

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☐ gas well ☐ other

2. NAME OF OPERATOR

Energetics, Inc.

3. ADDRESS OF OPERATOR

102 Inverness Terrace East, Englewood, CO 80112

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 680' FSL &amp; 1670' FEL

AT TOP PROD. INTERVAL: same

AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other)☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒5. LEASE  
N80-C-1420-17206. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Mountain Ute

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Ute 149. WELL NO.  
3410. FIELD OR WILDCAT NAME  
Verde Gallup11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 14, T31N, R15W12. COUNTY OR PARISH 13. STATE  
San Juan New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5605 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6-9-80: Rig up mast pole. Perforate at 100' with 2 jets. 6-10-80: MIRUPU-Farmington Well Service. Dump 2800# 20/40 sand down casing. Trip in hole with 2 3/8" tubing open ended and tag bridge at 510'. Circulate out same. Tag bridge at 1580'. Circulate out same. Tag top sand fill at 2190'. Spot 40 sacks class "B" cement plug from 1990-2190'. Good circulation. Lay down tubing. 6-11-80: Load hole with water. Cement 5 1/2" casing and 8 5/8" x 5 1/2" annulus with 30 sacks class "B" cement. Circulate one barrel cement. Rig down, move out pulling unit. 6-18-80: Install dry hole marker. 6-25-80: Clean location. Well plugged and abandoned.

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

Jack D. Cook

TITLE

Agent

DATE

8-28-80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY  
DENVER, COLO.