

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐
2. NAME OF OPERATOR
Energetics, Inc.
3. ADDRESS OF OPERATOR
102 Inverness Terrace East, Englewood, CO 80112
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 680' FSL & 1670' FEL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ ☐

FRACTURE TREAT ☐ ☐

SHOOT OR ACIDIZE ☐ ☐

REPAIR WELL ☐ ☐

PULL OR ALTER CASING ☐ ☐

MULTIPLE COMPLETE ☐ ☐

CHANGE ZONES ☐ ☐

ABANDON* ☐ ☒

(other) _____

5. LEASE N00-C-1420-1720	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME Mountain Ute	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME Ute 14	
9. WELL NO. 34	
10. FIELD OR WILDCAT NAME Verde Gallup	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 14, T31N, R15W	
12. COUNTY OR PARISH San Juan	13. STATE New Mexico
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 5605 GL	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-9-80: Rig up mast pole. Perforate at 100' with 2 jets. 6-10-80: MIRUPU-Farmington Well Service. Dump 2800# 20/40 sand down casing. Trip in hole with 2 3/8" tubing open ended and tag bridge at 510'. Circulate out same. Tag bridge at 1530'. Circulate out same. Tag top sand fill at 2190'. Spot 40 sacks class "B" cement plug from 1990-2190'. Good circulation. Lay down tubing. 6-11-80: Load hole with water. Cement 5 1/2" casing and 8 5/8" x 5 1/2" annulus with 30 sacks class "B" cement. Circulate one barrel cement. Rig down, move out pulling unit. 6-18-80: Install dry hole marker. 6-25-80: Clean location. Well plugged and abandoned.

Subsurface Safety Valve: Manu. and Type _____

18. I hereby certify that the foregoing is true and correct

SIGNED Jack D. Cook TITLE Agent DATE 8-28-80

(This space for Federal or State office use)

APPROVED BY David J. Miller TITLE Area Manager DATE FEB 24 1984

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

FEB 28 1984

OIL CON. DIV.
DIST. 3

*See Instructions on Reverse Side

SEP 2 1980

U. S. GEOLOGICAL SURVEY
FARMINGTON, COLO.