

NO. OF COPIES RECEIVED

DISTRIBUTION

SANTA FE

FILE

U.S.G.S.

LAND OFFICE

OPERATOR

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease

State ☐Fee ☒

5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Southland Royalty Company		8. Farm or Lease Name Mark Maddox
3. Address of Operator P. O. Drawer 570, Farmington, New Mexico		9. Well No. #1-A
4. Location of Well UNIT LETTER <u>J</u> , <u>1610</u> FEET FROM THE <u>South</u> LINE AND <u>1760</u> FEET FROM THE <u>East</u> LINE, SECTION <u>15</u> TOWNSHIP <u>32N</u> RANGE <u>11W</u> NMPM.		10. Field and Pool, or Wildcat Blanco Mesa Verde Blanco Pictured Cliffs
15. Elevation (Show whether DF, RT, GR, etc.) 6411' GL		12. County San Juan

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Spud and Casing report</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

6-7-78 Spudded 12-1/4" surface hole at 1:00 PM to a TD 240'. Ran 5 joints of 9-5/8", 36#, K-55 casing. Set at 236'. Cemented with 110 sacks Class "B" with 1/4# gel flake per sack and 3% CaCl₂. Plug down at 6:30 PM 6-7-78. Cement circ to surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

TITLE District Production ManagerDATE June 8, 1978

Original Signed by A. R. Kendrick

APPROVED BY

TITLE SUPERVISOR DIST. #3

DATE

CONDITIONS OF APPROVAL, IF ANY: