

30-045-23068

Page 1 Revised 10/01/78

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

OIL CONSERVATION DIVISION

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator E	BURLINGTON	RESOURC	ES OIL & GAS CO.		Lease	MADDOX MA	RK		Well No.	1A
Location										
of Well:	Unit J	Sect	15 Twp.	032N	Rge.	011W	County	SAN JUAN		
		NAME OF	RESERVOIR OR POO	L	T	YPE OF PROD.	METHO	D OF PROD.	PRO	DD. MEDIUM
						(Oil or Gas)	(Flow	or Art. Lift)	(Гbg. or Csg.)
Upper Completion	PICTURED	O CLIFFS				Gas	Flo	ow		Tubing
Lower Completion	MESAVER	RDE				Gas	Flo	ow		Tubing
			PRE-	FLOW SHUT-I	N PRES	SURE DATA			<u> </u>	
Upper	Hour, date s	hut-in	Length of time shut	SI press. psig		Stabilized? (Y		es or No		
Completion	07/26/2002		168 Hours		170		. (2-		ĺ	
Lower Completion	07/26	/2002	120 Hc	ours		175	:			
,				FLOW TE	EST NO.	1				
	at (hour,date)*		07/31/2002	07/31/2002			g (Upper or Lo	ower) LC	WER	
TIME	LAPSED TIME		PRESSURE			PROD. ZONE	E			
(hour,date)	nour,date) SINCE*		Upper Completion Lower Complet			TEMP	REM		MARKS	
08/01/2002	144	Hours	rs 171 80			:	turn on lower zone.			
08/02/2002	168	Hours	172	75			lower zo	one still flowing	ng	en gelekkej
!		.				:	turn on upper zone.			
									p t t t	
			:							
								<u> </u>	·	
Production rate	e during test									
Oil BOPD based on		Bbls. in		Hours	i.	Grav.		GOR	GOR	
Gas:			MCFPD; Tested thru (Orifice or Mete	er): 					
			MID-	TEST SHUT-II	N PRESS	SURF DATA				
Upper Completion	Hour, date s	hut-in	Length of time shut-in		SI press. psig			Stabilized? (Yes or No))
Lower Completion	Hour, date s	hut-in	Length of time shut	-in	SIp	press. psig	<u></u>	Stabilized? (Y	es or No)
4618301 388				(Continue or	reverse	side)	<u> </u>			

FLOW TEST NO. 2

ommenced at (hour, da	ate)**			Zone producing (Upper or Lov	ver):		
TIME	LAPSED TIME	PRESSURE		PROD. ZONE	DEMOKS.		
(hour, date)	SINCE "	Upper Completion	Lower Completion	TEMP.	REMARKS		
	 						
				-			
	-						
				Hours			
Jas			D. Tested and (e)				
Remarks:				·			
		•					
•		+		he best of my knowledge	·		
Approved	1.0011	200 2	9	Operator Burlingto	n Resources		
	Dil Conservation Div			By Odoro 1	lon		
OF		**************************************		Title Operations As	ssociate		
	WIY THE REST			Date Monday, Aug			

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data

24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.

8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).