UNITED STATES DEPARTMENT OF THE INTERIOR

5. LEASE	· •		21 G
SF 080376	6A		
6. IF INDIAN,	ALLOTTEE (OR TRIB	ENAME
		-	1 a 1
7. UNIT AGRE	EMENT NA	ME	
	4 7 7 7	<u> </u>	
8. FARM OR LI		:	<u>.</u>
_Sheets	5 1 8 <u>c</u>		요 한 표
9. WELL NO.	¥ = 5 = 1		D 1 7
_1A		<u></u>	% ₹ ½
10. FIELD OR W	ILDCAT NA	ME	=
Blanco Mes	a Verde)	\$ 17 g
11. SEC., T., R., AREA Sec	•		
12. COUNTY OF	R PARISH	13. ST	ATE
San Juan		New N	<u>lexico</u>
14. API NO.		£. :	
15. ELEVATION	S (SHOW	DF, KD	B, AND WD

DEFARTMENT OF THE INTERIOR	<u> </u>				
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME				
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME				
1. oil gas well other	Sheets				
2. NAME OF OPERATOR EL PASO NATURAL GAS CO.	1A STELD OR WILDCAT NAME				
3. ADDRESS OF OPERATOR BOX 289, FARMINGTON, NEW MEXICO	Blanco Mesa Verde 11. SEC., T., R., M., OR BLK. AND SURVEY OR				
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	AREA Sec. 28, T-31-N, R-9-W				
AT SURFACE: 1840'S, 800'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	12. COUNTY OR PARISH 13. STATE San Juan New Mexico 14. API NO.				
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)				
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6131' GL * \$ 1				
FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL GREAT GREA	(NOTE: Report results of multiple completion or zone				
PULL OR ALTER CASING	change on Form 9–330.)				
(other)					

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1/22/79: Spudded well. Drilled surface hole.

1/23/79: Ran 5 joints 9 5/8", 32.3#, H-40 surface casing, 197' set at 209'. Cemented with 224 cu. ft. cement. Circulated to surface. WOC 12 hours, held 600#/30 minutes.

Subsurface Safety Valve: Manu. and Typ	9		TO Set	(1) (1) (1) (1) (1) (1) (1) (1) (1) (1)	in support	_ Ft
18. I hereby certify that the foregoing is	true and correct тітье _Drilling_Clerk_	_ DATE	1/25/79), dx 100 0 00 400		
	(This space for Federal or State office us	e)		= =	等 差量	
APPROVED BYCONDITIONS OF APPROVAL, IF ANY:	TITLE	DATE .	<u> </u>	3 n	<u>ランゴ、</u> 変数する	