

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1840'S, 800'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>		<input checked="" type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>		<input checked="" type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>		<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>		<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>		<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>		<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>		<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>		<input type="checkbox"/>
(other)			

5. LEASE
SF 080376A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Sheets

9. WELL NO.
1A

10. FIELD OR WILDCAT NAME
Blanco M.V.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 28, T-31-N, R-9-W
N.M.P.M.

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6131' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1-29-79: TD 3395'. Ran 83 jts. 7", 20#, K-55 intermediate casing, 3383' set at 3395'. Cemented w/394 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement at 1400'.

2-02-79: TD 5662'. Ran 75 jts. 4 1/2", 10.5#, K-55 casing liner, 2419' set 3243-5662'. Float collar set 5645'. Cemented w/417 cu. ft. cement. WOC 18 hours.

4-06-79: PBTD 5645'. Tested casing to 3500#, OK. Perfed 5195, 5216, 5220, 5234, 5238, 5260, 5266, 5272, 5278, 5284, 5301, 5305, 5338, 5352, 5374, 5394, 5409, 5430, 5455, 5462, 5479, 5517, 5586' w/1 SPZ. Fraced w/72,500# 20/40 sand and 145,000 gal. water. Flushed w/7090 gal. water. Perfed 4478, 4484, 4716, 4722, 4740, 4766, 4784, 4800, 4806, 4812, 4818, 4824, 4907, 4930, 4973, 5080, 5088, 5096' w/1 SPZ. Fraced w/61,000# 20/40 sand and 122,000 gal. water. Flushed w/6340 gal. water.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. G. Dueso TITLE Drilling Clerk DATE April 9, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Gymock

