

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

Form Approved  
Budget Bureau No. 42-R1424

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR

EL PASO NATURAL GAS CO.

3. ADDRESS OF OPERATOR

BOX 289, FARMINGTON, NEW MEXICO

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1480'N, 1800'E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☒

☒

☒

☐

☐

☐

☐

☐

5. LEASE SF 081155	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
7. UNIT AGREEMENT NAME Allison Unit	
8. FARM OR LEASE NAME Allison Unit	
9. WELL NO. 53	
10. FIELD OR WILDCAT NAME Blanco MV	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 29, T-32-N, R-6-W NMPM	
12. COUNTY OR PARISH San Juan	13. STATE New Mexico
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 6457' GL	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

10/10/78: T.D. 3688'. Ran 91 joints 7", 20# KS intermediate casing, 3676' set at 3688'. Cemented with 308 cu. ft. cement. WOC 12 hours; held 1200#/30 minutes. Top of cement at 2300'.

10/15/78: T.D. 6108'. Ran 73 joints 4 1/2", 10.5#, KS casing liner, 2598' set 3510-6108'. Float collar set at 6091'. Cemented with 452 cu. ft. cement. WOC 18 hours.

10/28/78: PBTD 6091'. Tested casing to 3500#, OK. Perfed 5498, 5504, 5580, 5587, 5634, 5681, 5687, 5694, 5700, 5706, 5718, 5724, 5235, 5741, 5763, 5784, 5786, 5810, 5866, 5918, 5960, 6022, 6044 with 1 SPZ. Fraced with 153,000# 20/40 sand and 156,612 gal. water. Flushed w/7350 gal.wtr.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED D. A. Suico

TITLE Drilling Clerk

DATE 10/30/78

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

RECEIVED

NOV 2 1978

\*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY

