STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

6600501

327

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Well BURLINGTON RESOURCES OIL & GAS CO. Operator Lease REESE MESA No. 2A Location of Well: Unit Sect 11 Twp. 032N W800 Rge. SAN JUAN County NAME OF RESERVOIR OR POOL TYPE OF PROD. METHOD OF PROD. PROD. MEDIUM (Oil or Gas) (Flow or Art. Lift) (Tbg. or Csg.) Upper PICTURED CLIFFS Gas Flow Tubing Completion Lower **MESAVERDE** Gas Artificial Tubing Completion PRE-FLOW SHUT-IN PRESSURE DATA Upper Hour, date shut-in Length of time shut-in SI press. psig Stabilized? (Yes or No) Completion 08/31/2001 96 Hours 498 Lower Completion 08/31/2001 144 Hours 257 FLOW TEST NO. 1 Commenced at (hour.date)* 09/04/2001 Zone producing (Upper or Lower) **UPPER** TIME LAPSED TIME PRESSURE PROD. ZONE (hour.date) SINCE* **Upper Completion** Lower Completion TEMP REMARKS 09/05/2001 302 265 120 Hours turn on upper zone 09/06/2001 192 144 Hours 272 OIL CON. DIV DIST. 3 Production rate during test Oil BOPD based on Bbls. in Hours. Grav. GOR MCFPD: Tested thru (Orifice or Meter): Gas MID-TEST SHUT-IN PRESSURE DATA Upper Hour, date shut-in Length of time shut-in SI press. psig Stabilized? (Yes or No) Completion Lower Hour, date shut-in Length of time shut-in SI press. psig Stabilized? (Yes or No) Completion

(Continue on reverse side)

FLOW TEST NO. 2

Commenced at (hour, date)**				Zone producing (Upper or Lower):	
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE	REMARKS
		Upper Completion	Lower Completio	n TEMP.	REMARKS
	1	-			
	 	.d	·	<u></u>	
Production rate du	iring test				
Oil·	R	OPD based on	Bhls in	Hours	Grav GOR
Gas:		MCFP	D: Tested thru (C	Orifice or Meter):	
Damarke					
ixemarks.					
-			_	the best of my knowledg	е.
Approved	2FL18	2001 1	9	OperatorBurlingte	on Resources
	Oil Conservation Div			01	σ .
				By Alono A	logs
R. GRENALS	EWARD BY CHARAT	T. PERKIN		Title Operations A	ssociata
		NSPECTOR, BIST. #		Thre Operations A	SSUCIALE
Title		NOFELIUM, BISI 🦨	3 	Date Wednesday, S	September 12, 2001

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following: recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall north the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- 3 The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4 For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5 . Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above
- 6 Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1 Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows. 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclision of each flow period. 7-day tests: immediately prior to the beginning of each flow period at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8 The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).