	Budget Bureau No, 42-R1424
UNITED STATES	5. LEASE 1978 1978 1978 1978 1978 1978 1978 1978
DEPARTMENT OF THE INTERIOR	SF 078096
GEOLOGICAL SURVEY	- BATO SALE
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	
1 oil	_ 8. FARM OR LEASE NAME 이 전상 문화 Mudge 이 공유 가 드 이 하는
well well a other	9. WELL NO. 4 2 3
2. NAME OF OPERATOR El Paso Natural Gas Company	15A (PM)
3. ADDRESS OF OPERATOR	Blanco P.C. & Blanco M.V.
P.O. Box 289, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK, AND SURVEY OR
 LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 	AREA Sec. 8, T-31-N, R-11-W
AT SURFACE: 1150'S, 810'E	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	_ 14. APINO. 월월3 한 국 정말했는 ************************************
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6060' GL
TEST WATER SHUT-OFF	b b b ol
SHOOT OR ACIDIZE	
REPAIR WELL	(NOTE: Report results of multiple completion or zone change on Form 9-330.)
MULTIPLE COMPLETE	
CHANGE ZONES	Same of south of the second se
(other)	
measured and true vertical depths for all markers and zones pertine	ent to this work.)* 월양철물 월 월 월 월 월
surface casing, 208' set at 222'.	e. Ran 5 jts, 9 5/8", 36#, K-55
surface casing, 208' set at 222'.	e. Ran 5 jts, 9 5/8", 36#, K-55 Cemented w/224 cu. ft. cement.
surface casing, 208' set at 222'.	e. Ran 5 jts, 9 5/8", 36#, K-55 Cemented w/224 cu. ft. cement.
surface casing, 208' set at 222'.	e. Ran 5 jts, 9 5/8", 36#, K-55 Cemented w/224 cu. ft. cement.
surface casing, 208' set at 222'.	e. Ran 5 jts, 9 5/8", 36#, K-55 Cemented w/224 cu. ft. cement.
surface casing, 208' set at 222'.	e. Ran 5 jts, 9 5/8", 36#, K-55 Cemented w/224 cu. ft. cement.
surface casing, 208' set at 222'.	e. Ran 5 jts, 9 5/8", 36#, K-55 Cemented w/224 cu. ft. cement.
surface casing, 208' set at 222'. Circulated to surface. WOC 12 hou	e. Ran 5 jts, 9 5/8", 36#, K-55 Cemented w/224 cu. ft. cement.
surface casing, 208' set at 222'. Circulated to surface. WOC 12 hour Subsurface Safety Valve: Manu. and Type	e. Ran 5 jts, 9 5/8", 36#, K-55 Cemented w/224 cu. ft. cement.
surface casing, 208' set at 222'. Circulated to surface. WOC 12 hour Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct	e. Ran 5 jts, 9 5/8", 36#, K-55 Cemented w/224 cu. ft. cement. rs; held 600#/30 minutes of bar woleo modulated bis woleo modulated bis how a lange of anither bis woleo modulated bis how a non-anital bis of the second state of the bis how a non-anital bis of the bis how a non-anital bis bis woleo modulated bis how a non-anital bis of the bis
Subsurface Safety Valve: Manu. and Type	e. Ran 5 jts, 9 5/8", 36#, K-55 Cemented w/224 cu. ft. cement. rs; held 600#/30 minutes; and have of guide and have of g
surface casing, 208' set at 222'. Circulated to surface. WOC 12 hour Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct	e. Ran 5 jts, 9 5/8", 36#, K-55 Cemented w/224 cu. ft. cement. rs; held 600#/30 minutes; and have of guide and have of g
Subsurface Safety Valve: Manu. and Type	e. Ran 5 jts, 9 5/8", 36#, K-55 Cemented w/224 cu. ft. cement. rs; held 600#/30 minutes; and
Subsurface Safety Valve: Manu. and Type	e. Ran 5 jts, 9 5/8", 36#, K-55 Cemented w/224 cu. ft. cement. rs; held 600#/30 minutes; and
Subsurface Safety Valve: Manu. and Type	e. Ran 5 jts, 9 5/8", 36#, K-55 Cemented w/224 cu. ft. cement. rs; held 600#/30 minutes; and
Subsurface Safety Valve: Manu. and Type	e. Ran 5 jts, 9 5/8", 36#, K-55 Cemented w/224 cu. ft. cement. rs; held 600#/30 minutes; and addited bill of the work of the
Subsurface Safety Valve: Manu. and Type	e. Ran 5 jts, 9 5/8", 36#, K-55 Cemented w/224 cu. ft. cement. rs; held 600#/30 minutes; and addited bill of the work of the
Subsurface Safety Valve: Manu. and Type	e. Ran 5 jts, 9 5/8", 36#, K-55 Cemented w/224 cu. ft. cement. rs; held 600#/30 minutes; and addited bill of the work of the

. .