

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
2. NAME OF OPERATOR  
El Paso Natural Gas Company  
3. ADDRESS OF OPERATOR  
Box 289, Farmington, New Mexico 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1150'S, 810'E  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:  
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) <input type="checkbox"/>	

5. LEASE  
SF 078096  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Mudge  
9. WELL NO.  
15A (PM)  
10. FIELD OR WILDCAT NAME  
Blanco P.C. & Blanco M.V.  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 8, T-31-N, R-11-W  
N.M.P.M.  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6060' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9-16-79: PBDT 5333'. Tested casing to 3500#, OK. Perfed M.P.L. & P.L. 4903, 4912, 4926, 4934, 4944, 4950, 4956, 4962, 4968, 4974, 4984, 4990, 4995, 5000, 5011, 5027, 5034, 5040, 5050, 5069, 5080, 5114, 5134, 5178, 5228, 5253'. W/1 SPZ. Fraced w/ 90,500# 20/40 sand, 181,000 gal. wtr. Flushed w/ 6,636 gal. wtr. Perfed Men. 4614, 4649, 4674, 4706, 4735, 4781, 4825, 4837' W/1 SPZ. Fraced w/ 24,500# 20/40 sand, 49,000 gal. wtr. Flushed w/ 6,205 gal. wtr. Perfed P.C. 2697-2714, 2714-2731, 2738-2753, 2760-2773' W/1 SPZ. Fraced w/ 62,500# 20/40 sand, 72,500 gal. wtr. Dropped 3 sets of 16 balls ea. Flushed w/ 4,746 gal. wtr.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_

18. I hereby certify that the foregoing is true and correct

SIGNED A. D. Buico TITLE Drilling Clerk DATE Sept. 17, 1979

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

*mymoc*