

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐  
2. NAME OF OPERATOR  
EL PASO NATURAL GAS COMPANY  
3. ADDRESS OF OPERATOR  
P.O. BOX 289, FARMINGTON, N.M. 87401  
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1670'N, 1985' W  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5-08-79: TD 3156'. Ran 77 jts. 7", 20#, K-55 intermediate casing, 3144' set at 3156'. Cemented w/515 cu.ft. cement. WOC 12 hrs, held 1200#/30 min. Top of cement 1400'.

5-12-79: TD 5457'. Ran 76 jts. 4 1/2", 10.5#, K-55 casing liner, 2455' set 3002-5457'. Float collar set at 5440'. Cemented w/426 cu.ft. cement. WOC 18 hrs.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*D. G. Buisco*

TITLE

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

Drilling Clerk

DATE

5-31-79

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

NMOCC