

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

Form Approved.
Budget Bureau No. 42-R1424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
El Paso Natural Gas Company
3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, New Mexico 87401
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1300'S, 2230'E
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF ☐	☒
FRACTURE TREAT ☐	☐
SHOOT OR ACIDIZE ☐	☐
REPAIR WELL ☐	☐
PULL OR ALTER CASING ☐	☐
MULTIPLE COMPLETE ☐	☐
CHANGE ZONES ☐	☐
ABANDON* ☐	☐
(other) ☐	☐

5. LEASE
SE 078096
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Mudge
9. WELL NO.
12A (PM)
10. FIELD OR WILDCAT NAME
Blanco P.C. Ext. - Blanco M.V.
11. SEC., T., R., M. OR BLK. AND SURVEY OR AREA
Sec. 17, T-31-N, R-11-W, N.M.P.M.
12. COUNTY OR PARISH
San Juan
13. STATE
N.M.
14. API NO.

15. ELEVATIONS (SHOW DE KDB, AND WD)
6315' GA

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-21-79: Spudded well. Drilled surface hole. Ran 5 joints 9 5/8" 36#, K-55 surface casing, 207' set at 221'. Cemented with 224 cu.ft. cement. Circulated to surface. WOC 12 hours; held 600#/30 minutes.
6-26-79: TD 3236'. Ran 80 joints 7", 20#, K-55 intermediate casing, 3224' set at 3236'. Cemented w/459 cu.ft. cement. WOC 12 hours, held 1200#/30 minutes. Top of cement 2200'.
7-1-79: TD 5632'. Ran 88 joints 4 1/2" 1015# K-55 casing liner, 2597' set 3035-5632'. Float collar set at 5615'. Cemented w/441 cu.ft. cement. WOC 18 hours

Subsurface Safety Valve: Manu. and Type Set @ 1070

18. I hereby certify that the foregoing is true and correct

SIGNED D. P. Busco TITLE Drilling Clerk DATE July 5, 1979

(This space for Federal or State office use)

APPROVED BY NYMOCC TITLE DATE
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

APPROVED
JUL 9 1979
James T. Lima
District Engineer