

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1560'N, 1685'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input checked="" type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)		

5. LEASE
SF 078096

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Mudge

9. WELL NO.
14A (PM)

10. FIELD OR WILDCAT NAME
Aztec PC Ext. & Blanco M.V.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 21, T-31-N, R-11-W
N.M.P.M.

12. COUNTY OR PARISH
San Juan

13. STATE
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5904' G.L.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

- 9-21-79: Pressure tested to 3500#. Ran Cement Bond Log. Perfed one squeeze hole at 4718'. Set RTTS packer at 4500'. Cemented w/ 118 cu. ft. cement. WOC.
- 9-22-79: Ran Cement Bond Log. Perfed one squeezed hole at 4523'. Set RTTS packer at 4308'. Cemented w/ 118 cu. ft. cement. WOC
- 9-24-79: PBSD 5213'. Perfed P.L. & Men. 4523,4530,4544,4553,4610,4718,4755,4761,4767, 4772,4784,4790,4804,4810,4816,4822,4847,4865,4872,4892,4922,4964,4978,5029,5052, 5090,5103,5151' W/1 SPZ. Fraced w/ 106,500# 20/40 sand, 213,000 gal. wtr. Flushed w/5,838 gal. wtr. Perfed 2514-2526,2530-2540,2546-2562,2571-2580,2592-2600, 2616-2634' W/14 SPZ. Fraced w/ 73,500# 10/20 sd, 83,500 gal. wtr. Dropped 5 sets of 14 ball ea. (Found that only 23 balls dropped from ball dropper). Flushed w/ 4,284 gal. wtr.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. G. Busco TITLE Drilling Clerk DATE 9-28-79

(This space for Federal or State office use)

APPROVED BY _____ TITLE Drilling Clerk DATE September 28, 1979

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NMOCC