SHOOT OR ACIDIZE REPAIR WELL

ABANDON* (other)

PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES

100

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

	budget Bureau No. 42-R1424
5.	SF 078095
6.	IF INDIAN, ÁLLOTTEE OR TRIBE NAME
7.	UNIT AGREEMENT NAME
8.	FARM OR LEASE NAME Case
9.	WELL NO. 7 A
10.	FIELD OR WILDCAT NAME Blanco Mesa Verde
11.	SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 19, T-31-N, R-11

SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME		
1. oil gas other	8. FARM OR LEASE NAME Case		
well well wother 2. NAME OF OPERATOR El Paso Natural Gas Company	9. WELL NO. 7 A		
3. ADDRESS OF OPERATOR P.O. Box 289, Farmington, NM	10. FIELD OR WILDCAT NAME Blanco Mesa Verde		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 19, T-31-N, R NMPM		
AT SURFACE: 890'S, 950'E AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	12. COUNTY OR PARISH 13. STATE San Juan New Mexico		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	14. API NO.		
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF	ELEVATIONS (SHOW DF, KDB, AND WD) 5966' GL		
TEST WATER SHUT-OFF FRACTURE TREAT	69,		

DIST. 3

(NOTE: Report results of multiple completely

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 4-29-81: Tested casing to 3500#, Held OK. PBTD 5306'. Perfed P.L.:

4972,5000,5019,5033,5040,5062,5074,5137,5184,5211' W/1 SPZ. Fraced w/15,120#20/40 sand, 38,120 gal. wtr. Flushed w/6130gal. wtr.

Perfed Cliff House & Menefee: 4630,4653,4669,4676,4683,4738,4752,4798,4804,4812,4817,4824,4833,4840,4845,4849,4855,4861,4867,4873,4879,4889,4897,4908,4922,4930' W/1 SPZ. Fraced w/ 76,500# 20/40 sand, 104,750 gal. wtr. Flushed w/ 5925 gal. wtr.

Subsurface Safety Valve: Manu. a		•	Ft.		
18. I hereby certify that the forest	oing is true and correc	t Drilling	Clerk	Mav 4 l	981
SIGNED AV. J. SM		r Federal or State o			
APPROVED BY			DATE _	, etc	Firm FOR CZCORD

*See Instructions on Reverse Side

MAY 07 1981

