

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

M00-C-1420-1709

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Ute Mtn. Ute

7. UNIT AGREEMENT NAME

None

8. FARM OR LEASE NAME

Ute Mtn. Ute

9. WELL NO.

6

10. FIELD AND POOL, OR WILDCAT

Straight Canyon Dakota

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 14 - T31N - R16W
N.M.P.M.

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5767 GR 5772 KB

12. COUNTY OR PARISH

San Juan

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

Well History

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

☐
☐
☐
☒(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

The above captioned well was spudded 9-13-78. A 9 7/8" surface hole was mud drilled to a depth of 605'. 2 1/2" 9-15-78 approx. 591' of 7" 20# surface casing was set at 599' below KB and with 210 sx of Class B cement & 2% CaCl. Cement was circulated to the surface. B.O.P. was installed and surface was tested to 600 psig & held Ok for 15 min. On 9-16-78 commenced air drilling a 6 1/4" hole and drilled to 2370 + 5' to K.B. = 2375' on 9-18-78. There were no shows indicated while drilling to this depth. On 9-19-78 ran core barrel and cored from 2375 to 2401 and recovered core from 2375 to 2395'. 2375 to 2387 was mostly gray sh & siltstone. Dakota top at 2387 & from 2387 to 2395 was mostly gray, very fine grain silty & shaley sand with no show indicated. The bottom 6' of the core from 2395 to 2401 was not recovered. Went back to bottom with bit and air drilled without returns from 2401' to the T.D. of 2417' reached 9-20-78. 9-20-78 ran Induction-Gamma log and reached a depth of 2400'. Log tops as follows: Mesaverde at surface, Mancos top approx. 500'?, Gallup sand zone 1670, Sanastee 1904, Greenhorn 2267, Graneros 2330, Dakota 2387, T.D. log 2400. Plugging instructions were requested from the U.S.G.S. and on 9-20-78 the well was plug & abandoned as directed in the following manner: Hole was first mud circulated, then:

Across Dakota 100' cement plug pump placed 2400 up to 2300'

Across Gallup sd zone 150' cement plug pump placed 1850 up to 1700'
Across base of surf. 100' cement plug pump placed 650 up to 550'
30' cement plug at surf. & dryhole marker. Loc. to be restored as required

18. I hereby certify that the foregoing is true and correct

Agent for:

as soon as practical.

SIGNED

Ashton B. Geren, Jr.
Ashton B. Geren, Jr.

TITLE Robert C. Anderson

DATE Jan. 16, 1979

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side