

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐
2. NAME OF OPERATOR
Energetics, Inc.
3. ADDRESS OF OPERATOR 80112
102 Inverness Terrace East, Englewood, CO
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 890' FLS & 2000' FWL
AT TOP PROD. INTERVAL: Same
AT TOTAL DEPTH: Same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input checked="" type="checkbox"/>
(other) <input type="checkbox"/>	<input type="checkbox"/>

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-7-80 MIRUPU - Farmington Well Service. 6-9-80: Check PBTD to 2100'. Spot 40 sacks class "B" cement plug from 2100-1775'. Lay down 2 3/8" tubing. Rig up Go Wireline. Perforate at 100' with 2 shots. 6-10-80 Attempt to load hole to circulate 8 5/8" x 5 1/2" annulus. Dump 70 barrels total fluid - well on strong vacuum. Will have to reset bottom plug. 6-11-80 Run 66 joints 2 3/8" tubing and tag cement plug at 2007'. Pull tubing. Dump 2700# 20/40 mesh sand. Trip in hole with tubing and tag top sand at 1785'. Spot 40 sacks class "B" cement plug from 1785-1585'. Lay down 2 3/8" tubing. Circulate hole with water. Cement 5 1/2" casing and 8 5/8" x 5 1/2" annulus with 30 sacks class "B" cement. Circulate estimate 1/2 barrel cement. 6-18-80 Install dry hole marker. 6-26-80 Clean Up location. Well plugged and abandoned.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct


SIGNED Jack D. Cook TITLE Agent DATE 8-28-80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

5. LEASE MO 000-C-1420-1717	
6. IF INDIAN, ALLOTTEE OR TRIBE NAME Mountain Ute	
7. UNIT AGREEMENT NAME	
8. FARM OR LEASE NAME Ute 11	
9. WELL NO. 24	
10. FIELD OR WILDCAT NAME Verde Gallup	
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec 11, T31N, R15W	
12. COUNTY OR PARISH San Juan	13. STATE New Mexico
14. API NO.	
15. ELEVATIONS (SHOW DF, KDB, AND WD) 5790 GL	

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



*See Instructions on Reverse Side

U. S. GEOLOGICAL SURVEY
DURANGO, COLO.

State