

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐  
well well other
2. NAME OF OPERATOR  
Energetics, Inc.
3. ADDRESS OF OPERATOR 80112  
102 Inverness Terrace East, Englewood, CO
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1930' FSL & 410' FEL  
AT TOP PROD. INTERVAL: same  
AT TOTAL DEPTH: same
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input checked="" type="checkbox"/>
(other)	<input type="checkbox"/>	<input type="checkbox"/>

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details and give pertinent dates including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

6-9-80: Rig up mast pole. Perforate at 100' with 2 jets. 6-14-80 Farmington Well Service. Run 79 joints 2 3/8" tubing at 2455'. Dump 2400# 20/40 sand down 5 1/2" casing. Trip in hole with tubing bridge at 480'. Wash down with water. Tag top sand fill at 2391'. Spot 40 sacks class "B" cement plug from 2389-2189. Land tubing. Load hole with water. Cement 5 1/2" casing and 5 1/2" and 8 5/8" annulus with 30 sacks class "B" cement. Circulate estimate 3 barrels. 6-18-80 Install dry hole marker. 6-25-80 Clean up location. Well plugged and abandoned.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED Jack D. Cook TITLE Agent DATE 8-28-80  
Jack D. Cook  
(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

State

5. LEASE not  
N00-C-1420-1719

6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
Mountain Ute

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Ute 13

9. WELL NO.  
43

10. FIELD OR WILDCAT NAME  
Verde Gallup



11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec 13, 31N, 15W

12. COUNTY OR PARISH 13. STATE  
San Juan New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5763 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



SEP 9 1980

U. S. GEOLOGICAL SURVEY  
Ft. Collins, COLO.