UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE NOO-C-1420-1719
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME Mountain Ute 6 - 45
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9-331-0 for such proposals.)	7. UNIT ACREEMENT NAME: TO BE A SEE TO BE
1. oil gas well other	Ute 13 8 x 8 8 x 8 8 9. WELL NO. \$1.5 8 9.00
2. NAME OF OPERATOR Energetics, Inc.	9. WELL NO. \$137 \$ 000 \$ 43 55 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
3. ADDRESS OF OPERATOR 80112 102 Inverness Terrace East, Englewood, CO	Verde Gallup 2 11. SEC., T. R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 be ow.)	AREA 318 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8
AT SURFACE: 1930' FSL & 410' FEL AT TOP PROD. INTERVAL: same	12. COUNTY OR PARISH 13. STATE S San Juan 12. New MExico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	14. API NO. STATE TO THE TENT OF THE TENT
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF [] [] FRACTURE TREAT [] [] SHOOT OR ACIDIZE [] [] REPAIR WELL [] PULL OR ALTER CASING [] [] MULTIPLE COMPLETE [] [] CHANGE ZONES [] ABANDON* [] (other)	(NOTE: Report results of multiple completion or zone change on Form 9–330.) To the body of the change of the body of the change of the body of the bod
 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is dimeasured and true vertical depths for all markers and zones pertinen 6-9-80: Rig up mast pole. Perforate at 100' w Farmington Well Service. Run 79 joints 2 3/8" Dump 2400# 20/40 sand down 5 1/2" casing. Trip bridge at 480'. Wash down with water. Tag top sacks class "B" cement plug from 2389-2189. La Cement 5 1/2" casing and 5 1/2" and 8 5/8" annu cement. Circulate estimate 3 barrels. 6-18-80 6-25-80 Clean up location. Well plugged and a 	ith 2 jets. 2.6-14-80 MIRUPU tubing at 2455 Pull tubing in hole with tubing. Taga; sand fill at 2391'. Spot 40 nd tubing. Load hole with water. lus with 30 sacks class "B" in Install dry hole marker.

Subsurface Safety Valve; Manu, and Type

18. Thereby certify that the foregoing is true and correct

8-28-80

DURANGO, COLO.

(This space for Federal or State office use)

APPROVED BY David J. Miller

_ TITLE CON MANGEN DATE

FEB 24 1984

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side





OIL CON. DIV. DIST. 3