

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☒ other ☐

2. NAME OF OPERATOR
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR
P.O. Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1560'S, 800'W
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ ☒

FRACTURE TREAT ☐ ☒

SHOOT OR ACIDIZE ☐ ☐

REPAIR WELL ☐ ☐

PULL OR ALTER CASING ☐ ☐

MULTIPLE COMPLETE ☐ ☐

CHANGE ZONES ☐ ☐

ABANDON* ☐ ☐

(other) ☐ ☐

5. LEASE
SF078389A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME
San Juan 32-9 Unit

8. FARM OR LEASE NAME
San Juan 32-9 Unit

9. WELL NO.
100

10. FIELD OR WILDCAT NAME
Blanco PC-Ext.

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 12, T-31-N, R-10-W
N.M.P.M.

12. COUNTY OR PARISH
San Juan

13. STATE
N.M.

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
6354'GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

6-8-79: TD 3332'. Ran 109 joints. 2 7/8", 6.4#, J-55 production casing, 3321' set at 3321' set at 3332'. Cemented with 731 cu.ft. cement. WOC 18 hours.

6-13-79: Shot 1 squeeze hole at 3170'. Cemented w/147 cu.ft. cement.

6-14-79: Shot 1 squeeze hole at 3150'. Cemented w/59 cu.ft. cement.

6-15-79: Shot 1 squeeze hole at 3140'. Cemented w/59 cu.ft. cement.

6-22-79: Tst casing to 4000#, OK. TBTD 3321', Perfed PC 3174-3186, 3200-3213, 3213-3226, 3254-3264, 3297-3306'. w/12 SPZ. Fraced w/60,000# 20/40 sand and 53,000 gal. of slick water. Dropped 4 sets of 12 balls each. Flushed w/900 gal. of water.

RECEIVED

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED A. D. Guisco TITLE Drilling Clerk DATE July 5, 1979

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

NYMOCC

James T. Lewis
ACTING DISTRICT ENGINEER

