## UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

5.	LE	ASE
;	SF	078459-B

6 JEINDIAN ALLOTTEE OD TOUDE NAM

SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME Allison Unit
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME Allison Unit
1. oil gas Mell other  2. NAME OF OPERATOR	<b>9.</b> WELL NO. 16 A
El Paso Natural Gas Company  3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Blanco M.V.
Box 289, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 15, T-32-N, R-7-W N.M.P.M.
below.) 1180'N, 1620'W AT SURFACE:	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	San Juan New Mexico
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	14. AFT NO.
REPORT, OR OTHER DATA  REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6572' G.L.
TEST WATER SHUT-OFF	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinents.  79: Spudded well. Drilled surface hole. Ran 5 j casing 204' set at 214'. Cemented w/224 cu. WOC 12 hours; held 600#/30 minutes.	irectionally drilled, give subsurface locations and not to this work.)*  oints 9 5/8", 36#, K-55 surface
including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinents.  79: Spudded well. Drilled surface hole. Ran 5 j casing 204' set at 214'. Cemented w/224 cu.	irectionally drilled, give subsurface locations and not to this work.)*  oints 9 5/8", 36#, K-55 surface
including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinents.  79: Spudded well. Drilled surface hole. Ran 5 j casing 204' set at 214'. Cemented w/224 cu.	irectionally drilled, give subsurface locations and not to this work.)*  ioints 9 5/8", 36#, K-55 surface ft. cement. Circualted to surface
including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinents.  79: Spudded well. Drilled surface hole. Ran 5 j casing 204' set at 214'. Cemented w/224 cu. WOC 12 hours; held 600#/30 minutes.  Subsurface Safety Valve: Manu. and Type  18. I hereby certify that the foregoing is true and correct	intectionally drilled, give subsurface locations and not to this work.)*  ioints 9 5/8", 36#, K-55 surface ft. cement. Circualted to surface
including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinents.  79: Spudded well. Drilled surface hole. Ran 5 j casing 204' set at 214'. Cemented w/224 cu. WOC 12 hours; held 600#/30 minutes.  Subsurface Safety Valve: Manu. and Type	irectionally drilled, give subsurface locations and not to this work.)*  soints 9 5/8", 36#, K-55 surface ft. cement. Circualted to surface.
including estimated date of starting any proposed work. If well is d measured and true vertical depths for all markers and zones pertinents.  79: Spudded well. Drilled surface hole. Ran 5 j casing 204' set at 214'. Cemented w/224 cu. WOC 12 hours; held 600#/30 minutes.  Subsurface Safety Valve: Manu. and Type  18. I hereby certify that the foregoing is true and correct	Set @Ft.  DATEAugust 28, 1979

\*See Instructions on Reverse Side

SEP 11 1979