UNITED STATES

DEPARTMENT OF THE INTERIOR	SF 078509
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME San Juan 32-9 Unit 8. FARM OR LEASE NAME
1. oil gas 🔀 other	San Juan 32-9 Unit 9. WELL NO.
2. NAME OF OPERATOR El Paso Natural Gas Company	32A 10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR P.O. Box 289, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 790'N, 800'W AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	Blanco M.V. 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 31, T-32-N, R-9-W N.M.P.M. 12. COUNTY OR PARISH 13. STATE San Juan New Mexico 14. API NO.
6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6629' GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE CHEPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly stating including estimated date of starting any proposed work. If well is a measured and true vertical depths for all markers and zones pertine	directionally drilled, give subsurface locations and
5-19-79: Spudded well. Drilled surface hole	
5-20-79: Ran 5 jts. 9 5/8", 36#, K-55 surface with 228 cu. ft. cement. Circulate 600#/30 minutes.	ce casing, 205' set at 219'. Cemented ed to surface. WOC 12 hours; held MAY 2 2 1979 OIL CON. COM. DIST. 3
Subsurface Safety Valve: Manu. and Type	Set @
18. I hereby certify that the foregoing is true and correct	는 사람들은 기계를 가는 것이 되었다. 사람들은 기계를 보고 있다. 기계를 보고 있다.
SIGNED DE DELISCO TITLE DEILLING C	lerk DATE May 21, 1979
(This space for Federal or State o	ffice use)
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	DATE TO THE TOTAL TO THE T

5. LEASE

*See Instructions on Reverse Side