Dec. 1973	Form Approved. Budget Bureau No. 42–R1424
UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	S.J. 32-9 Unit 8. FARM OR LEASE NAME
1. oil gas X other	S.J. 32-9 Unit
2. NAME OF OPERATOR	<u>38A</u>
El Paso Natural Gas Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR Box 289, Farmington, N.M. 87401	Blanco M.V. The second
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA Sec. 35, T-32-N, R-10-W
below.) AT SURFACE: 1880'S, 720'E	N.M.P.M.
AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE San_Juan New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	<u> </u>
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 66571 G.L.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	
SHOOT OR ACIDIZE	
	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
PULL OR ALTER CASING	
	· · · · · · · · · · · · · · · · · · ·
ABANDON*	· · · · · · · · · · · · · · · · · · ·
(other)	· · · · · · · · · · · · · · · · · · ·
measured and true vertical depths for all markers and zones pertine	· 발생한 · · · · · · · · · · · · · · · · · · ·
6-6-79: Spudded well. Drilled surface hole surface casing, 288' set at 302'. Circulated to surface. WOC 12 hour	Cemented with 316 cu. ft. cement.
surface casing, 288' set at 302'.	Cemented with 316 cu. ft. cement.
surface casing, 288' set at 302'.	Cemented with 316 cu. ft. cement.
surface casing, 288' set at 302'.	Cemented with 316 cu. ft. cement.
surface casing, 288' set at 302'.	Cemented with 316 cu. ft. cement.
surface casing, 288' set at 302'.	Cemented with 316 cu. ft. cement.
surface casing, 288' set at 302'. Circulated to surface. WOC 12 hour	Cemented with 316 cu. ft. cement. s; held 600#/30 minutes. s; held 600#
surface casing, 288' set at 302'. Circulated to surface. WOC 12 hour Subsurface Safety Valve: Manu. and Type	Cemented with 316 cu. ft. cement.
Subsurface Safety Valve: Manu. and Type	Cemented with 316 cu., ft., cement. s; held 600#/30 minutes. a soft contained with a soft contained of contained and contained and a soft contained and co
Subsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct	Cemented with 316 cu., ft., cement. s; held 600#/30 minutes. a soft contained with a soft contained of contained and contained and a soft contained and co
Subsurface Safety Valve: Manu. and Type Bubsurface Safety Valve: Manu. and Type 18. I hereby certify that the foregoing is true and correct SIGNED (This space for Federal or State of	Cemented with 316 cu. ft. cement. s; held 600#/30 minutes. add add add add add add add add add add
Subsurface Safety Valve: Manu. and Type	Cemented with 316 cu. ft. cement. rs; held $600\#/30$ minutes. f(r) = rk DATE $6-111-79$ Ft. $r = r = r = r = r = r = r = r = r = r$
Subsurface Safety Valve: Manu. and Type	Cemented with 316 cu. ft. cement. rs; held $600\#/30$ minutes. The second seco
Subsurface Safety Valve: Manu. and Type	Cemented with 316 cu. ft. cement. rs; held $600\#/30$ minutes. f(r) = 100% for a standard of the standard

3