

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-2995

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Burnt Mesa

9. WELL NO.

#2A

10. FIELD AND POOL, OR WILDCAT
So Los Pinos Frt PC Ext.
Blanco Mesa Verde11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 26, T32N, R7W

12. COUNTY OR PARISH 13. STATE

San Juan

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL ☐ GAS ☒
WELL WELL OTHER

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

P. O. Drawer 570, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1090' FSL & 1560' FEL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6732' GR

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

Casing Report

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)*

6-25-79

Set 94 joints (3862') of 7", 20#, K-55, ST & C casing at 3874'.
Cemented with 160 sacks of Class "B", 50/50 Poz with 6% gel followed by
50 sacks of Class "B" with 2% CaCl₂. Plug down at 8:00 PM, 6-25-79.

6-29-79

Set 62 joints (2604') of 4 1/2", 10.5#, K-55, ST & C casing from 3719'
to 6336'. Cemented with 305 sacks of Class "B", 50/50 Poz with 6% gel,
1/4# cello flake and .6% Halad 9. Plug down at 3:30 PM, 6-29-79.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE District Production Manager DATE 7-2-79

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

mymo

