API#

STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

Page 1 Revised 10/01/78

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

Operator I	ו ופו וו	NGTON	N RESOUR	`ES () &	GAS CO		Lease	BURNT MESA	\	Well No.	2A
Operator	JUKLII	NGTO	1 INESCON	JEO OIL G				= -			
Location of Well:	Unit	0	Sect NAME O	26 F RESERVO	Twp. 03 DIR OR POOL	2N	Rge.	007W YPE OF PROD. (Oil or Gas)	County SAN JU METHOD OF PR (Flow or Art. Li	OD. P	PROD. MEDIUM (Tbg. or Csg.)
Upper Completion	PI	CTURE	D CLIFFS		· · · · · · · · · · · · · · · · · · ·			Gas	Flow		Tubing
Lower Completion	ME	SAVE	RDE					Gas	Flow		Tubing
Upper Completion			shut-in 11/00	Length	PRE-FLOV n of time shut-in 120 Hours	V SHUT-IN		SURE DATA press. psig 445	Stabilize	d? (Yes or 1	No)
Lower Completion	1	8/11/00			72 Hours	FLOW TE	ST NO.	445 			
Commenced at (hour,date)* TIME LAPSED TIME (hour,date) SINCE*				Upper	8/14/00 Zone producing (Upper or Lower) LOWER PRESSURE PROD. ZONE Upper Completion Lower Completion TEMP REMARKS						
8/15/00		96	Hours		445	221					
8/16/00		120	Hours		450	189	0300	12.65			
						18 14 15 TG	St. Co.	AUG 2000			
			·								
Production r	ate dur	ing test						معتمد المعتمد المعتمد			
Oil:		ВС	OPD based or	1	Bbls. in		Hou	rs.	Grav.		GOR
Gas:			-	MCFPI); Tested thru (Ori	ifice or Met	er):				
						ST SHUT-I		SSURE DATA		. 10 (37 -	- No.
Upper Completio		lour, da	te shut-in	Leng	th of time shut-in		SI	press. psig		zed? (Yes o	_
Lower Completio	F	lour, da	te shut-in		th of time shut-in		SI	press. psig	Stabiliz	zed? (Yes o	r No)
708402	361				(Continue of	n revers	e side)			

FLOW TEST NO. 2

Commenced at (hour, d	ate)**		TEOW TEST IN						
		T		Zone producing (Upper or Lower):					
TIME (hour, date)	LAPSED TIME SINCE **	Upper Completion	SSURE Lower Completion	PROD. ZONE TEMP.	REMARKS				
		oppor completion	Lower Completion						
	<u>[</u>								
Production rate dur	ring test								
Oile	P.O.	DD 1							
Oii.	BO	PD based on	Bbls. in _	Hours	GravGOR				
Gas:		MCFPE): Tested thru (Orit	fice or Meter):					
									
I hereby certify that	the information here	ein contained is true	and complete to th	e best of my knowledge	<u>.</u>				
	AUG 2 5 21	JUU		_					
Approved	l Conservation Divisi	19	' 	Operator Burlingto	n Resources				
New Mexico Of	I Conservation Divisi	ion		By Alan L	Page 0				
ORIGINAL	L SIGNED BY CHAR	LET PERMI		ANTO A					
Ву				Title Operations Associate					
Title	OIL & GAS INSPECT	FOR. DIST 🚁	,						
				Date Wednesday, A	ugust 23, 2000				

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed weil within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- 2. At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note, if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7 Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only)