

| | |
|------------------------|---|
| NO. OF COPIES RECEIVED | 4 |
| DISTRIBUTION | |
| SANTA FE | 1 |
| FILE | |
| U.S.G.S. | |
| LAND OFFICE | |
| OPERATOR | 2 |

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

| |
|------------------------------------------------------------------------------------------------------|
| 5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/> |
| 5. State Oil & Gas Lease No. K5808 |
| 7. Unit Agreement Name |
| 8. Farm or Lease Name Albino Canyon |
| 9. Well No. #2 |
| 10. Field and Pool, or Wildcat Albino PC Ext. |
| 12. County San Juan |

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER

2. Name of Operator
Southland Royalty Company

3. Address of Operator
P. O. Drawer 570, Farmington, NM 87401

4. Location of Well
UNIT LETTER L 1610' FEET FROM THE South LINE AND 790' FEET FROM
THE West LINE, SECTION 36 TOWNSHIP 32N RANGE 8W NMPM.


15. Elevation (Show whether DF, RT, GR, etc.)
6956' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

| | |
|------------------------------------------------|-------------------------------------------------------------------------|
| NOTICE OF INTENTION TO: | SUBSEQUENT REPORT OF: |
| PERFORM REMEDIAL WORK <input type="checkbox"/> | REMEDIAL WORK <input type="checkbox"/> |
| TEMPORARILY ABANDON <input type="checkbox"/> | COMMENCE DRILLING OPNS. <input type="checkbox"/> |
| PULL OR ALTER CASING <input type="checkbox"/> | CASING TEST AND CEMENT JOB <input type="checkbox"/> |
| OTHER <input type="checkbox"/> | OTHER <u>Spud and Casing Report</u> <input checked="" type="checkbox"/> |

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-14-79 Spudded 12 1/4" surface hole at 12:15 PM, 5-14-79 and drilled to a TD of 160'. Set 4 joints (141.65') of 8 5/8", 26#, K-55, 8 rd casing at 153'. Cemented with 165 sacks of Class "B" with 1/4# flocele per sack and 3% CaCl₂. Cement circulated to surface. Plug down at 7:00 PM, 5-14-79.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE District Production Manager DATE 5-15-79

Original Signed by A. R. Kendrick SUPERVISOR DISTRICT # 3 DATE MAY 17 1979

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY: