

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM-6893

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Wilmer Canyon

9. WELL NO.

#2

10. FIELD AND POOL, OR WILDCAT

Blanco MV

N Los Pinos Frt

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 25, T32N, R8W

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

1.

OIL ☐ GAS ☒
WELL WELL OTHER

2. NAME OF OPERATOR

Southland Royalty Company

3. ADDRESS OF OPERATOR

P. O. Drawer 570, Farmington, NM 87401

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)

At surface

1170' FNL & 1800' FWL

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6931' GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Perforation & Stimulation

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-1-79 Perforated the Mesa Verde at 5857', 5902', 5908', 5914', 5920', 5926', 5932', 5938', 5944', 5950', 5956', 6016', 6052', 6056', 6153', 6164', 6173', 6184', 6199', 6209', 6226'. Total of 21 holes. Brokedown with 1,575 gallons of 15% HCL and balls. Fracd the Mesa Verde with 156,702 gallons of water and 131,000 # of 20/40 sand. AIR 36, ATP 200, ISIP 1700. Set retrievable bridge plug at 3995'. Spotted 210 gallons of 15% HCL. Perforated the Pictured Cliffs at 3719', 3725', 3759', 3812', 3819', 3826', 3833', 3840', 3847', 3854', 3861', 3868'. Total of 12 holes. Brokedown with 900 gallons of 15% HCL and balls. Fracd the Pictured Cliffs with 65,247 gallons of water and 44,100 # of 20/40 sand. AIR 22, ATP 2300, ISIP 900.



18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE District Production Manager

DATE

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side