

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 078243

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

ARNSTEIN

9. WELL NO.

1-M

10. FIELD AND POOL, OR WILDCAT

EASIN DAKOTA

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

SEC. 18 T-31N R-12W

12. COUNTY OR PARISH

SAN JUAN

13. STATE

N.M.

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER	
2. NAME OF OPERATOR CONSOLIDATED OIL AND GAS, INC.	
3. ADDRESS OF OPERATOR P.O. BOX 2038 FARMINGTON, NEW MEXICO 87401	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1065' FNL AND 1791; FNL SEC. 18 T-31N R-12W	
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 5929 GR

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

FRAC IN 2 STAGES1ST STAGE DK

3-22-80 PERF 7011, 12-13-14-15-16-17-18-19-20-21-22-23-24-25.

3-24-80 ACIDIZED W/1000 GAL. 15% N.E. ACID. FRAC WITH 52,920 GAL. CROSSLINK GEL AND 26,000# 100 MESH SAND & 40,000# 20-40 SAND. MAX PRES. 6100#. Avg. PRES. 5000#. avg. INJ. RATE= 8.5 BPM.

2ND STAGE DK

3-27-80 PERF 6802, 06-10-14-29-34-38-46-61-71-75-79-88-96-9900-04-36-51-64.

3-28-80 ACIDIZED W/1500 GAL. 15% N.E. ACID. FRAC W/ 133,000 GAL CROSSLINK GEL AND 33,000# 100 MESH AND 137,000# 20-40 SAND. MAX. PRES. 3800#, AVG. PRES. 3300#, AVG. INJ. RATE = 42 BPM.

4-1-80 SET BAKER MODEL "E" PRODUCTION PACKER AT 6740'



18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE DRLG. SUPT.

DATE 4-17-80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Tops

PC 2120

mv 3841

DK 6797