

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐

2. NAME OF OPERATOR

Caribou Four Corners, Inc.

3. ADDRESS OF OPERATOR

2906 1st Ave N. Billings, Montana 59101

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 890' FSL & 600' FEL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☒

(other) ☐

SUBSEQUENT REPORT OF:

☐

☐

☐

☐

☐

☐

☐

☐

☐

5. LEASE

MOB-C-1426-1950

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Ute

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Ute Mountain

9. WELL NO.

#2

10. FIELD OR WILDCAT NAME

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec 21, T31N, R15W

12. COUNTY OR PARISH 13. STATE

San Juan


New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

5682 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Verbal approval obtained 5-11-81 to P & A as follows:

1. Spot 22 sx Cement plug from PBTD of 2304 to 2050'.
2. Shoot off casing near 1000' and recover 4½" casing.
3. Run tubing and spot 20 sx plug from 950' to 1050' (across base of 7")  
If cannot shoot off casing will perforate 4½" casing and place 50' plug of cement between 4½" & 7" and leave 50' plug in 4½".
4. Place 10 sx cement plug 50' to surface.
5. Run 1" down 9 5/8" X 7" and cement 50' to surface.
6. Install standard dry hole marker.

This work will be performed 5-12-81.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED John L. Price TITLE Petroleum Eng. DATE 5-11-81

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE District Supervisor DATE 5/14/81  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_