UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	5. LEASE SF 078097 6. IF INDIAN, ALLOTTEE OR TRIBE NAME 7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)			
1. oil gas well other 2. NAME OF OPERATOR	Heaton 9. WELL NO. 4A		
El Paso Natural Gas Company 3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Blanco Mesa Verde		
Box 289, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 29, T-31-N, R-11-W N.M.P.M. 12. COUNTY OR PARISH 13. STATE San Juan New Mexico 14. API NO.		
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	15. ELEVATIONS (SHOW DF, KDB, AND WD) 5980 ' GL		
FRACTURE TREAT X	.		

Box 289, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See spa below.) 1825'S, 930'E AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NO REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT O TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (NOTE: Report results of multiple completion or zone PULL OR ALTER CASING change on Form 9-330.) MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* PBTD 5207'. Tested casing to 3500#, OK. Perfed 4604,4619,4627,4646, 1-29-80: 4668, 4676, 4801, 4818, 4824, 4829, 4834, 4854, 4864, 4870, 4875, 4881, 4886, 4906,4919,4942,4984,5029,5036,5048,5054,5068,5110'. W/1 SPZ. Fraced w/86,500# 20/40 sand, 166,500 gal. wtr. Flushed w/5880. gal. wtr.

Subsurface Safety Valve: Manu. and Type			Set @	.Ft.
18. I hereby certify that the foregoing is				
SIGNED A. J. SHE CO	TITLE Drilling Clerk	DATE	Jarusty 130 , 1980	
	(This space for Federal or State office us	se)	FEB 11980	
APPROVED BY	NMOCC	DATE _	OIL CON. COM. DIST. 3	-