

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other

2. NAME OF OPERATOR  
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR  
P.O. Box 209, Farmington, NM

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1600'N, 1635'W  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:


TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) ☐

SUBSEQUENT REPORT OF:

☐  
☒  
☐  
☐  
☐  
☐  
☐  
☐  
☐

RECEIVED  
MAY 18 1981  
U.S. GEOLOGICAL SURVEY  
FARMINGTON, N.M.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)



5. LEASE  
NM 021124

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Newberry

9. WELL NO.  
13A

10. FIELD OR WILDCAT NAME  
Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 17, T-31-N R-12-W  
NMPM

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5956' GL

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5-12-81: PBTD 5124'. Tested casing to 3500#, OK. Perfed Lower P.L.:  
4858,4863,4875,4884,4893,4898,4906,4914,4919,4929,4934,4950,4956,  
4966,4985,5005,5051'W/1 SPZ. Fraced w/ 39,500# 20/40 sand, 51,430  
gal. wtr. Flushed w/6050 gal. wtr.

5-13-81: Perfed Massive P.L.:  
4554,4560,4614,4710,4720,4726,4732,4738,4744,4750,4756,4766,4771,  
4776,4785,4790,4808,4814,4820' W/1 SPZ. Fraced w/ 48,000# 20/40  
sand, 96,000 gal. wtr. Flushed w/ 5721 gal. wtr.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. G. Busco TITLE Drilling Clerk DATE May 13, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY: \_\_\_\_\_

NMOCC'

\*See Instructions on Reverse Side

RECEIVED FOR ALLOC.

MAY 18 1981

FARMINGTON DISTRICT

BY 2