

## SUNDRY NOTICES AND REPORTS ON WELLS

1. oil well ☐ gas well ☒ other

2. NAME OF OPERATOR  
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR  
Box 289, Farmington, New Mexico 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
 AT SURFACE: 870 'S, 840 'E  
 AT TOP PROD. INTERVAL:  
 AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,  
REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>
(other)	<input type="checkbox"/>

SUBSEQUENT REPORT OF:

X
.

RECEIVED

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

APR 15 1980

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4-4-80: TD 2869'. Ran 66 joints of 7", 20#, K intermediate casing 2858' set at 2869'. Cemented w/482 cu. ft. cement. WOC 12 hours;held 1200#/30 minutes. Top of cement 1550'.

4-8-80: TD 5326'. Ran 82 joints 4 1/2", 10.5#, K-55 casing liner 2595' set 2731-5326'. Float collar set at 5308'. Cemented w/ 477 cu. ft. cement WOC 18 hours.

ACCEPTED FOR RECORD

APR 16 1980

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

**18. I hereby certify that the foregoing is true and correct**

SIGNED D. P. Duse TITLE Drilling Clerk DATE April 11, 1980

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

APR 17 1980  
OIL CON. COM.  
DIST. 3

**\*See Instructions on Reverse Side**

**NMOCC**

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐  
well well

2. NAME OF OPERATOR  
El Paso Natural Gas Company

3. ADDRESS OF OPERATOR  
P.O. Box 289, Farmington, NM 87401

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 870'S, 840'E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) ☐

SUBSEQUENT REPORT OF:

☐

☒

☐

☐

☐

☐

☐

☐

☐

RECEIVED  
MAY 29 1981  
U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

5. LEASE  
SF 078146

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME  
Newberry

9. WELL NO.  
6A

10. FIELD OR WILDCAT NAME  
Blanco Mesa Verde

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 17, T-31-N, R-12-W  
NMPM

12. COUNTY OR PARISH  
San Juan

13. STATE  
New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
6074' GL

NOTE: Report results of multiple completion of zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

5-15-81: PBTD 5308'. Tested casing to 3500#, OK Perfed Lower P.L.  
4984,5008,5016,5030,5036,5048,5053,5058,5090,5110,5175,  
5188' w/1 SPZ. Fraced w/ 24,000# 20/40 sand, 48,000 gal. wtr.  
Flushed w/6138 gal. wtr.

5-16-81: Perfed Massive P.L. & Cliff House & Menefee:  
4672,4678,4684,4837,4850,4858,4863,4867,4872,4877,4882,4900,4906,  
4914,4918,4937,4944' w/1 SPZ. Fraced w/43,000# 20/40 sand, 86,000  
gal. wtr. Flushed w/ 5922 gal. wtr.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED A. D. Davis TITLE Drilling Clerk DATE May 21, 1981

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

\*See Instructions on Reverse Side

NMOCC

JUN 01 1981  
BY Dean Elliott  
FARMINGTON DISTRICT