STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

This form is not to be used for reporting packer leakage tests in Southeast New Mexico

## OIL CONSERVATION DIVISION

AUG 2000
RECEIVED

30-045-23872

Page 1 Revised 10 01/78

## NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

perator BI	URLINGTON RESOURCE	ES OIL & GAS CO.	Lease RICHARDSC	ON	No. 10E
ocation f Well:	Unit L Sect	10 Twp. 031N	Rge. 012W	County SAN JUAN	
		RESERVOIR OR POOL	TYPE OF PROD.	METHOD OF PROD.	PROD. MEDIUM
			(Oil or Gas)	(Flow or Art. Lift)	(Tbg. or Csg.)
Upper Completion	FRUITLAND		Gas	Flow	Tubing
Lower Completion	DAKOTA		Gas	Flow	Tubing
		PRE-FLOW SI	HUT-IN PRESSURE DATA		
Upper	Hour. date shut-in	Length of time shut-in	SI press. psig	Stabilized? (Yes or No)	
Completion	5/19/00	72 Hours	247		
Lower Completion	5/19/00	120 Hours	211		
			OW TEST NO. 1		
Commenced at (hour.date)* 5/22/00			Zone producing (Upper or Lower) UPPER		
TIME LAPSED TIME		PRESSURE	PROD. ZON		4.DVC
(hour.date)	SINCE*	Upper Completion Lower	r Completion TEMP	REN	1ARKS
5/23/00	96 Hours	179	211		
5/24/00	120 Hours	179	211		
Production rat	e during test				
Dil:	BOPD based on	Bbls. in	Hours.	Grav.	GOR
Gas:	MCFPD; Tested thru (Orifice or Me				
		MID-TEST S	HUT-IN PRESSURE DATA		
Upper Completion	Hour, date shut-in	Length of time shut-in	SI press. psig	Stabilized? (	Yes or No)
Lower Completion	Hour. date shut-in	Length of time shut-in	SI press. psig	Stabilized? (	Yes or No)
660002 38	7	(Cont	tinue on reverse side)		

## FLOW TEST NO. 2

Commenced at (hour, da	nte)**		Zone producing (Upper or Lower):						
TIME (hour, date)	LAPSED TIME SINCE **	PRESSURE		PROD. ZONE	DEMANA				
		Upper Completion	Lower Completion	on TEMP.	REMARKS				
Production rate during test  Oil:BOPD based onBbls. inHoursGravGOR  Gas:MCFPD: Tested thru (Orifice or Meter):									
Remarks:									
I hereby certify that the information herein contained is true and complete to the best of my knowledge.									
ApprovedAUG 2 8 200019 Operator Burlington Resources									
New Mexico Oi	l Conservation Divis	sion		By Olors.	Rein				
By	. Sighed by Char	LE T. PERAIN	Title Operations Associate						
Title	OIL & GAS INSPE	CTOR, DIST. #8		Date Thursday, August 24, 2000					

## NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- 1. A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and annually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- 6. Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1 Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows. 3 hours tests: immediately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Aztec District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).