

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

SF 0784-39

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Johnston-Federal

9. WELL NO.

15

10. FIELD AND POOL, OR WILDCAT

Blanco

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREA

Section 35-T31N-R9W

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

6000' GL

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

WELL STATUS

X

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 3200'. 5-1/2" casing set at 3196'. PBD 3145'. Perforated 2792-98', 2802-10' with 1 SPF. Acidized w/750 gals. 15% HCL. ISIP-700 psi; 5 min.-450 psi. Foam fraced 2792-98', 2802-10' with 6552 75 quality foam and 3840# 10/20 sand. Sanded off at 3700 psi w/3500# sand in formation.

Presently cleaning up after frac and flow testing.



18. I hereby certify that the foregoing is true and correct

SIGNED

S.A. Hiraoka

TITLE

Petroleum Engineer

DATE

1/22/81

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

NMOCC

*See Instructions on Reverse Side

BW