UNITED STATES

UNITED STATES	5. LEASE <u>មិខិ</u> ទ្ធ ខ្លួន ខេន្ត ខេន
DEPARTMENT OF THE INTERIOR	SF 080517
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
- Controlling Cont	O. LVIVIII OIL FENDE INVINCE TO THE PARTY OF
1. oil gas X other	9. WELL NO. 229 2 222
2. NAME OF OPERATOR	<u> 4-A 취로로의 을 발활성</u>
SUPRON ENERGY CORPORATION	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Basin Dakota - Blanco Mesaverde
P. O. Box 808, Farmington, New Mexico 8740	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
 LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 	Sec. 22, T-32N, R-10W, N.M.P.M.
AT SURFACE: 1100 ft./S; 135 ft./E line.	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL: Same as above.	San Juan New Mexico
AT TOTAL DEPTH: Same as above.	14. API NO. BARRETTO
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6901 R.K.B.
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	
FRACTURE TREAT	ì la varia National de Salata
SHOOT OR ACIDIZE	
PULL OR ALTER CASING	(NOTE: Report results of multiple completion or zone
MULTIPLE COMPLETE	SON TO THE PROPERTY OF THE PRO
CHANGE ZONES	
ABANDON*	
(other)	S STE ME STORY
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent of pertinent details, and give pertinent details de	
1. Spudded 13-3/4" surface hole at 5:15 A.M. 6	5/8/80. Disk to the beautiful of the bea
2. Drilled 13-3/4" hole to total depth of 559	ft. R.K.B. manual and a second
3. Ran 12 joints of 10-3/4", 32.75#, H-40 casi	ng and landed at 557 ft. R.K.B.
4. Cemented with 525 sacks of class "B" with 3	% calcium chlaride and 1//#
flocele per sack. Plug down at 6:00 A.M. 6	9/80. Cement circulated to surface.
	그 그 그 그 그는 그 이 이 이 이 이 이 이 이 이 이 이 이 이 이
5. Waited on cement 12 hours.	indicate and a second control of the
6. Pressure - tested casing to 800 P.S.I. for	20 minutes. Held O.K.
Subsurface Safety Valve: Manu. and Type	
18. I hereby certify that the foregoing is true and correct	2
SIGNED Kenneth E. Knowly Fittle Production Su	pt. DATE July 21, 1980 = 3
(This space for Federal or State office use)	
ADDO ARREST. IS FOR DECORD TITLE	고등하다. 발표 원칙원()
APPROACHED FOR RECORD TITLE TITLE	
	House of the control
AUG 04 1980	The state of the s

*See Instructions on Reverse Side

FARMINGTON DISTRICT