

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other

2. NAME OF OPERATOR  
Tenneco Oil Company

3. ADDRESS OF OPERATOR  
720 S. Colo. Blvd., Denver, CO 80222

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 1090'FNL, 1110'FEL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐  
(other) Report on Drilling Operations.

5. LEASE  
SF-078040  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME  
7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
Mudge Com B  
9. WELL NO.  
1  
10. FIELD OR WILDCAT NAME  
Basin Dakota  
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA  
Sec. 11; T31N; R11W  
12. COUNTY OR PARISH  
San Juan  
13. STATE  
New Mexico  
14. API NO.  
15. ELEVATIONS (SHOW DF, KDB, AND WD)  
5878'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

4/20/80

Spudded 13 3/4" hole @ 11:30AM 4/20/80. Ran and set 5 Jts 9 5/8", 36# csg @ 223. Cmt. w/175 sxs CL B w/3% CACL2. Circ. to surface. Reduced hole to 8 3/4" and resumed drilling. On 4/24, ran and set 85 jts of 7", 23# csg @ 3500'. Cmt w/630 sxs 50/50 Pozmix, 4% gel. Tailed w/150 sxs CL B w/2% CACL2. Circ to 120'. Reduced hole to 6 1/4" and drilled to TD of 7258'. Ran and set 121 jts. of 4 1/2", 10.5#, 11.6# csg @ 7258'. TOL: 3252. Cmt. w/350 sxs 50/50 Pozmix and tailed w/150 sxs CL-B. TOC: 3252'. Released rig 4/30. WOCU.

ACCEPTED FOR RECORD

MAY 12 1980

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

*Carly Hattman*

TITLE Admin. SUPERVISOR DATE 5/2/80

(This space for Federal or State office use)

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DATE

\*See instructions on Reverse Side

MAY 14 1980  
U.S. GEOLOGICAL SURVEY  
DIST. 3

U. S. GEOLOGICAL SURVEY  
FARMINGTON, N. M.

NMOCC