

NO. OF COPIES RECEIVED

DISTRIBUTION

SANTA FE

FILE

U.S.G.S.

LAND OFFICE

OPERATOR

## NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease

State ☐Fee ☒

5. State Oil &amp; Gas Lease No.

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

|  |  |  |
|--|--|--|
| 1. OIL <input type="checkbox"/> GAS <input checked="" type="checkbox"/> OTHER-<br>WELL WELL  |  | 7. Unit Agreement Name                         |
| 2. Name of Operator<br>Southland Royalty Company   |  | 8. Farm or Lease Name<br>Patterson "B" Com     |
| 3. Address of Operator<br>P. O. Drawer 570, Farmington, New Mexico 87401   |  | 9. Well No.<br>1-E                             |
| 4. Location of Well<br>UNIT LETTER <u>M</u> <u>805</u> FEET FROM THE <u>south</u> LINE AND <u>895</u> FEET FROM<br>THE <u>west</u> LINE, SECTION <u>2</u> TOWNSHIP <u>31N</u> RANGE <u>12W</u> NMPM. |  | 10. Field and Pool, or Wildcat<br>Basin Dakota |
| 15. Elevation (Show whether DF, RT, GR, etc.)<br>6219' GR  |  | 12. County<br>San Juan                         |

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐

PLUG AND ABANDON ☐  
CHANGE PLANS ☐

OTHER ☐

REMEDIATION WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER ☐

ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

Spud and Casing Report ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7-17-80 Spudded 12-1/4" surface hole at 1:00 P.M. 7-17-80 and drilled to Total Depth of 230'.

Ran 5 joints (210') of 9-5/8", 32.30#, H-40 casing set at 222'.

Cemented with 125 sacks of Class "B" with 1/4# gel flake per sack and 3% CaCl<sub>2</sub>.

Plug down at 6:45 P.M. 7-17-80.

Circulated cement to surface.



18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED

*R. E. Fildes*

TITLE

District Engineer

DATE July 18, 1980

APPROVED BY

Original Signed by FRANK T. CHAVEZ

SUPERVISOR DISTRICT #3

TITLE

DATE JUL 21 1980

CONDITIONS OF APPROVAL, IF ANY: