UNITED STATES

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	14-20-603-2034
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
	Navajo
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME To English
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)	<u> </u>
reservoir. Use Form 3-332-C for such proposals.)	8. FARM OR LEASE NAME A STANDARD Navajo 'F' 1886 A STANDARD NAVAJO 'F' 1886 A STANDARD NAVAJOR
1. oil gas control gas well other	9. WELL NO.
2. NAME OF OPERATOR	147 9 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5
Solar Petroleum, Inc.	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR CO 80202	Horseshoe Gallup
One Denver Place #1300, 999 18th St., Denver	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA 로뉴션을 바 발표되었다. 9-T31N-R1/7Wing 로 프라이션
below.)	
AT SURFACE: 80' FNL, 2580' FWL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE 그 San Juan 독자 등 New Mexico
AT TOTAL DEPTH:	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE.	14. API NO. Balling to be a subject to the subject
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
<i>*</i> '	5242'是GL会与广图
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	0 1 5 to
SHOOT OR ACIDIZE	t bar kena salah barakan salah
REPAIR WELL	(NOTE: Report results of multiple completion or zone
PULL OR ALTER CASING	change on Form 9-330.)
MULTIPLE COMPLETE	Approximation of the control of the
UTIANGE ZUIVES	
ABANDON SPUD DATE & CASING RECORD X	
(Other)	日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state	all pertinent details, and give pertinent dates,
including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*	
SPUD DATE: 2/14/81	
DATE TD REACHED: 2/17/81	불통학하는 한 성수성의 1912년 1일
DATE COMPLETED:	- And
TOTAL DEPTH: 1,070'	EFFE DOM. COM
	TO THE RESERVE TO THE PARTY OF
SET 8-5/8" casing with 100 sx Class 'B' Neat, 1	#/sx Flake, 3% cc (12-1" hole)
[100% returns with 3 bbls excess to surface]	@ 90'. 44 a a a a a a a a a a a a a a a a a a
	្តីត្រូវក្សា ខ្លុំ ខេត្តក្រី
SET $4-\frac{1}{2}$ " casing with 300 sx 50/50 POZ, 2% gel, 1	
last 150 sx (6- $\frac{1}{2}$ " hole) [20 sx in excess to s	sfc] @ 1,055% # # # # # # # # # # # # # # # # # #
Subsurface Safety Valve: Manu. and Type	Set @Ft.
18. I hereby certify that the foregoing is true and correct	(4) (4) (4) (4) (4) (4) (4) (4) (4) (4)
SIGNED May & Stine TITLE Sr. Pet. Engine	eer DATE May 27, 1981
(This space for Federal or State office use)	
APPROVED BY TITLE	DATE 178 1 5 5 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
APPROVED BY TITLE CONDITIONS OF APPROVAL, IF ANY:	BETS P. LELER BELLEVILLED
	CACAMOR NAMED AND ADDRESS OF THE PARTY OF TH
	1 1 4 - Em - A = 1981

*See Instructions on Reverse Side

JUN 0=1981

BY Sear Pllitt