LINITED STATES

Dec. 1373	UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE SF-077648		
	GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME		
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)		7. UNIT AGREEMENT NAME		
		8. FARM OR LEASE NAME		
1. oil 🖂	gas 📉	Davis		
well	well other	9. WELL NO.		
2. NAME OF OPERATOR		13-E		
Southland Royalty Company		10. FIELD OR WILDCAT N	.1	
3. ADDRESS OF OPERATOR P.O. Drawer 570, Farmington, N.M. 87401		Basin Dakota 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA		
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17		· ·	Section 1, T31N, R12W.	
below.)		12. COUNTY OR PARISH 13. STATE		
AT SURFACE: 1770' FSL & 880' FWL AT TOP PROD. INTERVAL:		San Juan		
AT TOTAL DEPTH:		14. API NO.	IVOV MOXICO	
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA		15. ELEVATIONS (SHOW DF, KDB, AND WD) 6361' GR		
REOUEST FOR	APPROVAL TO: SUBSEQUENT REPORT OF:	0001 011	n. Karay	
	EAT	CEIVED EP 19 19 19 19 19 19 19 19 19 19 19 19 19	SEPIRA OIL CON. CO DIST. 3	
including	E PROPOSED OR COMPLETED OPERATIONS (Clearly States) estimated date of starting any proposed work. If well is and true vertical depths for all markers and zones perting	ent to this work.)*	Januace locations dises	
9/06/80	Ran 129 joints (5113') of 7", 23#, K-55 casing set at 5098'. Cemented 1st Stage with 40 sacks of Class "B" 50/50 Poz with 6% gel, followed by 70 sacks of Class "B" Neat with 2% CaCl ₂ . Plug down at 6:00 P.M. 9-06-80. Cemented 2nd Stage with 165 sacks of Class "B" 50/50 Poz with 6% gel, followed by 70 sacks of Class "B" Neat with 2% CaCl ₂ . Plug down at 7:45 P.M. 9-06-80. TOC @ 1500'.			
9/10/80	Ran 69 joints (2678') of 4–1/2", $10.5\#$ & $11.6\#$, K–55 casing set from $4947'$ – $7637'$.			
9/11/80	Cemented with 320 sacks of Class "B" 50/50 Poz with 6% gel, 1/4# gel flake per sack and .6% Halad 9 and 6-1/4# gilsonite per sack. Plug down at 7:45 A.M. 9-11-80.			
Subsurface Sa	rety Valve: Manu. and Type	Set	: @ Ft.	
18. I hereby c	ertify that the foregoing is true and correct			
SIGNED	ACCEPTED FOR RECUMU TITLE Dist. Prod.	Mgr. DATE September	er 15, 1980	
	(This space for Federal or State	office use)		
APPROVED BY .	CED 1 7 1080			