UNITED STATES

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	SF-077651
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS	7. UNIT AGREEMENT NAME
Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas	Richardson
well well X other	9. WELL NO.
2. NAME OF OPERATOR	8-E 10. FIELD OR WILDCAT NAME
Southland Royalty Company	Basin Dakota/Blanco Pictured Cli
3. ADDRESS OF OPERATOR	11. SEC., T., R., M., OR BLK. AND SURVEY OR
P.O. Drawer 570, Farmington, New Mexico 87401	-1
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	Section 10, T31N, R12W
below.) AT SURFACE: 1590' FNL & 1070' FEL	12. COUNTY OR PARISH 13. STATE
AT TOP PROD. INTERVAL:	San Juan New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
CURCOUENT REPORT OF	6183' GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	
MULTIPLE COMPLETE CHANGE ZONES BABANDON* (other) Spud and Casing Report MU. S. GEOLOGICA FARMINGTON,	L SURVEY N. E.
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly statincluding estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertined.)	ent to this work.)*
June 7, 1980 Spudded 12-1/4" surface hole	at 12:01 P.M. 6-07-80 and
7 122 2 42 2271	
Ran 5 joints (201.52') of 9-5	0/8", 32.30#, π=40 Casing
set at 21 4'. Cemented with 110 sacks of Cl	lass "R" with 1/4# flocele
Cemented with 110 sacks of Ci	Lass D WICH I
per sack and 3% CaCl2.	an Affra
Plug down at 4:00 P.M. 6-07-8 Circulated cement to surface.	
Circulated Cement to Sullage	OIL CON. 1980 DIST. 30M. Ft.
Subsurface Safety Valve: Manu. and Type	Set @Ft.

Subsurface Safety Valve: Manu. and Typi	
18. I hereby certify that the foregoing is	rue and correctTITLE
	(This space for Federal or State office use)
APPROVED BY	TITLE DATE

NMOC?

AGGEPTED FOR REGORD

JUN 10 1980

*See Instructions on Reverse Side