

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE
(See other in-
structions on
reverse side)

FOR APPROVED
OMB NO. 1004-0187

Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.
SF-077651

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME, WELL NO.

Richardson #8E

9. API WELL NO.

30-045-24019

10. FIELD AND POOL, OR WILDCAT

Dusenberry Gallup/Basin Dakota

11. SEC., T., R., M., OR BLOCK AND SURVEY
OR AREA

Sec.10, T-31-N, R-12-W

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐

b. TYPE OF COMPLETION:

NEW WELL ☐ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☒ Other ☐

2. NAME OF OPERATOR

BURLINGTON RESOURCES OIL & GAS COMPANY

3. ADDRESS AND TELEPHONE NO.

PO BOX 4289, Farmington, NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)

At surface 1590'FNL, 1070'FEL

At top prod. interval reported below

At total depth

14. PERMIT NO.

DATE ISSUED

12. COUNTY OR
PARISH
San Juan

13. STATE

New Mexico

15. DATE SPUNDED
6-7-80

16. DATE T.D. REACHED
7-3-80

17. DATE COMPL. (Ready to prod.)
3-13-00

18. ELEVATIONS (DF, RKB, RT, BR, ETC.)
6183' GR

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD
7450'

21. PLUG, BACK T.D., MD & TVD
CIBP @ 7050'

22. IF MULTIPLE COMPL.
HOW MANY*

23. INTERVALS
DRILLED BY

ROTARY TOOLS

CABLE TOOLS

0-7450'

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*

5944-6920' Gallup

26. TYPE ELECTRIC AND OTHER LOGS RUN
IES, GR-Density, GR-Induction

27. WAS WELL CORED

NO

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8"	32.3#	218'	12 1/4"	110 sx	
7"	23#	4929'	8 3/4"	390 sx	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
4 1/2"	4761'	7448'	315 sx		2 3/8"	7010'	CIBP @ 7050'

30. TUBING RECORD

31. PERFORATION RECORD (Interval, size and number)

5944-5954', 5994-6004', 6073-6083', 6220-6230', 6280-6290', 6340-6350', 6900-6920'

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
5944-6083'	1420 bbl 35# lnr gel, 100,000# 20/40 AZ snd
6220-6350'	747 bbl 25# lnr gel, 62,365# 20/40 AZ snd
6900-6920'	531 bbl 25# lnr gel, 31,682# 20/40 Brady snd
Sqz holes @ 7120'	350 sx Class "B" 50/50 poz w/2% gel, .4% Halad-344,
	2% CFR-3, .1% HR-5 (441 cu ft).

33. PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type or pump)					WELL STATUS (Producing or shut-in)	
		Flowing					SI	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL-BBL	GAS-MCF	WATER-BBL	GAS-OIL RATIO	
3-13-00			→		123 Pitot gauge			
FLOW, TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL-BBL	GAS-MCF	WATER-BBL	OIL GRAVITY-API (CORR.)		
SI 480	SI 490	→						

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

None

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED

TITLE

Regulatory Administrator

DATE 3-20-00

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

APR 27 2000

RECEIVED FOR RECORD

INSTRUCTIONS

General: This form is designed for submitting a complete and correct well completion report and log on all types of lands and leases to either a Federal agency or a State agency, or both, pursuant to applicable Federal and/or State laws and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office. See instructions on items 22 and 24, and 33, below regarding separate reports for separate completions.

If not filed prior to the time this summary record is submitted, copies of all currently available logs (drillers, geologists, sample and core analysis, all types electric, etc.), formation and pressure tests, and directional surveys, should be attached hereto, to the extent required by applicable Federal and/or State laws and regulations. All attachments should be listed on this form, see item 35.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 18: Indicate which elevation is used as reference (where not otherwise shown) for depth measurements given in other spaces on this form and in any attachments.

Items 22 and 24: If this well is completed for separate production from more than one interval zone (multiple completion), so state in item 22, and in item 24 show the producing interval, or intervals, top(s), bottom(s) and name(s) (if any) for only the interval reported in item 33. Submit a separate report (page) on this form, adequately identified, for each additional interval to be separately produced, showing the additional data pertinent to such interval.

Item 29: "Sacks Cement": Attached supplemental records for this well should show the details of any multiple stage cementing and the location of the cementing tool.

Item 33: Submit a separate completion report on this form for each interval to be separately produced. (See instruction for items 22 and 24 above.)

37. SUMMARY OF POROUS ZONES:			38. GEOLOGIC MARKERS		
SHOW ALL IMPORTANT ZONES OF POROSITY AND CONTENTS THEREOF; CORED INTERVALS; AND ALL DRILL-STEM TESTS, INCLUDING DEPTH INTERVAL TESTED, CUSHION USED, TIME TOOL OPEN, FLOWING AND SHUT-IN PRESSURES, AND RECOVERIES			NAME	TOP	
FORMATION	TOP	MEAS. DEPTH		TRUE VERT. DEPTH	
Ojo Alamo	905'				
Furitland	2174'				
Pict. Cliffs	2550'				
Cliff House	4212'				
Pt. Lookout	5012'				
Gallup	6350'				
Greenhorn	7123'				
Graneros	7176'				
Dakota	7252'				