Form 9-331 Dec. 1973

HNITED STATES

_	Form A	pproved	 	<u> </u>
	Budget	Bureau		

DEPARTMENT OF THE INTERIOR	5. LEASE NM 012647				
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME				
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir, Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME				
1. oil gas well other	Case A 9. WELL NO.				
2. NAME OF OPERATOR Company	10. FIELD OR WILDCAT NAME				
3. ADDRESS OF OPERATOR 720 S. Colorado Blvd., Denver, CO 80222	Basin Dakota 11. SEC., T., R., M., OR BLK. AND SURVEY OR				
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 1680' FSL, 1010' FEL	AREA ST8 T31N R11W				
AT TOP PROD. INTERVAL: Unit I AT TOTAL DEPTH:	San Juan Rew Mexico				
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)				
REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF FRACTURE TREAT	6104 GR				
FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other) Plug and Sidetrack RECEIVED WAR 17 1980 U. S. GEOLOGICAL SURVEY.					
 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 3/12/80 On 3/7/80, received verbal approval from Jim Simms to plug and sidetrack fish in hole. The procedure to be used is as follows: 1) Run freepoint and back off. Drill collars at top of washpipe 0[±] 4878'. 2) Spot cement plug on top of the fish w/ sufficient cement to squeeze the Mesa Verde interval, and have cement plug 0[±]50' on constitutions are repeated in the procedure of cement to ensure that it is with place. 4) If cement is not in place, repeat step #2. 5) When cement is in place, spot 300' plug 0 base of 7" casing 183 g 1 lass B w/ 10/20 sand to sidetrack hole. 6) Redrill to TD using air mist. 					
18. I hereby ceptify that the foregoing is true and correct SIGNED WALLY WALLESTILE Ather. Suppr. DATE 3/12/80					
(This space for Federal or State off	Withnish				
APPROVED BY TITLE NMOCCI	MARE 2 DE 1988				

*See Instructions on Reverse Side DISTRICT OIL & CAS SUPERVISOR