UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

Dec. 1973	Budget Bureau No. 42-R1424
UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE SF-077652
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9-331-C for such proposals.)	8. FARM OR LEASE NAME
1. oil gas X other	East
well well other 2. NAME OF OPERATOR	9. WELL NO
Southland Royalty Company	10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR	Basin Dakota/Blanco Mesa Verde
P.O. Drawer 570, Farmington, New Mexico 87401	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 26, T31N, R12W
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)	
AT SURFACE: 1045' FSL & 1695' FWL AT TOP PROD. INTERVAL:	12. COUNTY OR PARISH 13. STATE San Juan New Mexico
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 6069' GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF SACTURE TREAT	

Southland Royalty Company 3. ADDRESS OF OPERATOR P.O. Drawer 570, Farmington, New Mexico 8740 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 1 AT SURFACE: 1045' FSL & 1695' FWL AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTIC REPORT, OR OTHER DATA SUBSEQUENT REPORT OF: REQUEST FOR APPROVAL TO: TEST WATER SHUT-OFF -RACTURE TREAT THOOT OR ACIDIZE PEPAIR WELL NOTE: Report results of multiple completion or zone PULL OR ALTER CASING change on Form 9-330.) MULTIPLE COMPLETE CHANGE ZONES ABANDON* Sidetrack uther) 17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, accounting estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* PROPOSE TO: Spot 100 sacks of Class "B" on top of fish (7024'-6550'), inside 6-3/4" open noie. POOH. WOC 3 hours. Re-cement as necessary to fill to 6550' NOC 18 hours. Dress off plug to 6580' to drill sidetrack hole Drill sidetrack hole to Total Depth of 7211'. VERBAL APPROVAL RECEIVED FROM ERROL BECHER ON 7-21-80. __ Set @ _ Ft. Subsurface Safety Valve: Manu. and Type THILE District Engineer DATE July 22, 1980

(This space for Federal or State office use)