TEST WATER SHUT-OFF FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL

PULL OR ALTER CASING

MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)

AND LONG

UNITED STATES DEPARTMENT OF THE INTERIOR **GEOLOGICAL SURVEY**

Dec. 1973	Budget Bureau No. 42-R1424
UNITED STATES DEPARTMENT OF THE INTERIOR	5. LEASE SF 078085
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
1. oil gas well other	8. FARM OR LEASE NAME Sunray 9. WELL NO.
2. NAME OF OPERATOR El Paso Natural Gas Company	6 10. FIELD OR WILDCAT NAME
3. ADDRESS OF OPERATOR P.O. Box 289, Farmington, NM 87401	Blanco Pictured Cliffs 11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) 1530'S, 830'E	AREA Sec. 21, T-31-N, R-10-W
AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	12. COUNTY OR PARISH 13. STATE San Juan New Mexico 14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD)
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	6209' GL

(NOTE: Report results of multiple completion or zone

change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

8-51-80: PBTD 3145'. Tested casing to 4000#, OK. Perfed 2975,2980,2985,3009,3013,3017, 3060,3065,W/1 SPZ. Fraced w/ 42,000# 10/20 sand, 51,910 gal. wtr. w/ 1980 gal. wtr. C. SECLOGICAL SURVEY FARMINGTON, N. M. Subsurface Safety Valve: Manu. and Type _ Set @ 18. I hereby certify that the foregoing is true and correct Drilling Clerk DATE (This space for Federal or State office use) ACCEPTED FOR RECORD APPROVED BY CONDITIONS OF APPROVAL, IF ANY: AUG 21 1980 FARMINGTON DISTRICT

*See Instructions on Reverse Side