

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
well well
2. NAME OF OPERATOR
Tenneco Oil Company
3. ADDRESS OF OPERATOR
720 S. Colo. Blvd., Denver, CO 80222
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 990'FNL, 990'FEL, Unit A
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

- TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

- (other) Status Report: Drilling

5. LEASE
SF-078097
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Heaton Com B
9. WELL NO.
2
10. FIELD OR WILDCAT NAME
Basin Dakota
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 30; T31N; R11W
12. COUNTY OR PARISH 13. STATE
San Juan New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
5938'GR

RECEIVED

FEB 23 1980

(NOTE: Report results of multiple completion or zone change on Form 9-330.)
U. S. GEOLOGICAL SURVEY
FARMINGTON, N. M.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
2/11-2/21/80

Spudded 12 1/4" hole at 4:00PM 2/11/80. Ran 5 jts of 9 5/8" 36# csg, set @235'. Cmt w/135 sxs CLB w/2% CACL2. Circ cmt to surface. Reduced hole to 8 3/4" 3400' where 77 jts of 7", 23# csg was set. Cmt w/525 sxs 50/50 Pozmix & 4% gel. Tail in w/150 sxs CLB w/2% CACL2. Circ. to surface. Test to 1000 psi. Reduced hole to 6 1/4" & resumed drilling. On 2/20, reached TD of 7080'. Ran & set 5 jts. of 4 1/2" 11.6# and 83 jts of 4 1/2" 10.5# csg and landed at 7067'. TOL: 3226. Cmt w/300 sxs 50/50 Pozmix and 150 sxs CLB w/.4% D-113. Circ. to surface PD. Released rig 2/21/80. WOCU.

Subsurface Safety Valve: Manu. and Type

18. I hereby certify that the foregoing is true and correct

SIGNED

Carly Station

TITLE

Admin. Supervisor

DATE

2/22/80

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

Set @ _____ Ft.

FEB 23 1980
U.S. GEOLOGICAL SURVEY
FARMINGTON, N.M.

ACCEPTED FOR RECORD

FEB 28 1980

FARMINGTON DISTRICT

BY

M. L. Kuchera