mark the st

UNITED STATES

UNITED STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	5. LEASE SF 078097 6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or plug back to a different eservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME
1. oil gas well other 2. NAME OF OPERATOR	Heaton 9. WELL NO. 6A
El Paso Natural Gas Company 3. ADDRESS OF OPERATOR Box 289, Farmington, New Mexico 87401 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: AT TOP PROD. INTERVAL: AT TOTAL DEPTH: 6. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	10. FIELD OR WILDCAT NAME Blanco Mesa Verde 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 33, T-31-N, R-11-W NMPM 12. COUNTY OR PARISH San Juan New Mexico 14. API NO.
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 5885' GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: FERCTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES ABANDON* (other)	(NOTE: Report results of multiple completion or zone change on Form 9–330.)

including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TD 2806'. Ran 64 joints of 7", 20#, K-55 intermediate casing 2794' set at 2806'. Cemented w/ 417 cu. ft. cement. WOC 12 hours;held 1200#/30 minutes. Top of cement at 700'.

3-31-80: TD 5126'. Ran 77 joints of 4 1/2", 10.5#, K-55 casing liner 2464' set 2662-5126'. Float collar set at 5108'. Cemented w/ 437 cu. ft. cement WOC 18 hours.

Subsurface Safety Valve: Manu. and Type ____ 18. I hereby certify that the foregoing is true and correct April 1, 1980 Drilling Clerk DATE (This space for Federal or State office use) _ TITLE . APPROVED BY CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side