STATE OF NEW MEXICO ENERGY and MINERALS DEPARTMENT

DEPAR IMENT

This form is not to
be used for reporting
packer leakage tests
in Southeast New Mexico

Completion

OIL CONSERVATION DIVISION

BITT

30-045-24198

API#

Page 1 Revised 10/01/78

NORTHWEST NEW MEXICO PACKER-LEAKAGE TEST

										OWN 3	ົ້ປິ Well	ó.
DI	LIDLING	TON	BESOUR	CES (1) S	0.00		Lease	PHILLIPS CO	· · · · · · · · · · · · · · · · · · ·		Well No.	1E
perator B	URLING	- ION	RESOUR	CES OIL 6	S OIL & GAS CO.			PHILLIPS COM		The subject of the su		-
ocation												
f`Well:	Unit	K	Sect	23	Twp.	031N	Rge.	013W	County	SAN JUAN		
			NAME C	of reserv	OIR OR POO	L	Т	YPE OF PROD.	METH	IOD OF PROD.	1	OD. MEDIUM
								(Oil or Gas)		(Flow or Art. Lift)		Tbg. or Csg.)
Upper Completion	DAK	ATC						Gas	Flow T		Tubing	
Lower Completion	FRUITLAND							Gas	Flow			Casing
					PRE-	FLOW SHUT-I	N PRES	SURE DATA				
Upper	Hour, date shut-in			Leng	Length of time shut-in			SI press. psig		Stabilized? (Yes or No)		·)
Completion		4/23/99			120 Hours			105				
Lower Completion	4/23/99			72 Ho	urs	330						
						FLOW TI	EST NO.	1				
Commenced	at (hou	,date)*			4/26/99			Zone producing	g (Upper or	Lower) LC	WER	
TIME	LAPSED TIME				PRESSURE			PROD. ZONE				
(hour,date)	SINCE*		Uppe	r Completion	Lower Completion		ТЕМР	RE		MARKS		
4/27/99	96 Hours			128	0			Flow lower zone.				
4/28/99	120 Hours			130	0			Logged-off				
								Logged-off :END TEST				
	-											
	<u> </u>											
	<u> </u>								_			
roduction rate	e during	test										
Dil:	BOPD based on			·	Bbls. in			Hours.		Grav. GOR		
ias:				MCFP.	D; Tested thru	(Orifice or Met	er): _					
					МТГ	-TEST SHUT-I	N PRES	SURE DATA				
Upper Completion	Hour, date shut-in Length of time shut-in					SI press. psig			Stabilized? (Yes or No)			
	Unus data shut in			I am	Langth of time shut-in			nress nsig	Stabilized? (Yes or No)			

FLOW TEST NO. 2

Commenced at (hour, da	ate)**		Zone producing (Upper or Lower):					
TIME	LAPSED TIME	PRES	SURE	PROD. ZONE				
(hour, date)	SINCE **	Upper Completion	Lower Completion		REMARKS			
Production rate dur	ring test							
Oil:	BC	PD based on	Bbls. in	Hours	GravGOR			
Gas:		MCFPL MCFPL): Tested thru (Or	ifice or Meter):				
Remarks:								
I hereby certify that	t the information her	ein contained is true	and complete to t	the best of my knowledge				
	OCT 13							
			·	Operator Burlington	Resources			
New Mexico Oi	l Conservation Divis	ion		De Albert	Page 12			
ORIGI	NAL SIGNED BY CH	HAPLUET PERFON		By AMORD L				
Ву			Title Operations Associate					
Title	Y OIL & GAS INSPE	ector, dist. 🚜		Date Tuesday, June 15, 1999				

NORTHWEST NEWMEXICO PACKER LEAKAGE TEST INSTRUCTIONS

- A packer leakage test shall be commenced on each multiply completed well within seven days after actual completion of the well, and arnually thereafter as prescribed by the order authorizing the multiple completion. Such tests shall also be commenced on all multiple completions within seven days following recompletion and/or chemical or fracture treatment, and whenever remedial work has been done on a well during which the packer or the tubing have been disturbed. Tests shall also be taken at any time that communication is suspected or when requested by the Division.
- At least 72 hours prior to the commencement of any packer leakage test, the operator shall notify the Division in writing of the exact time the test is to be commenced. Offset operators shall also be so notified.
- The packer leakage test shall commence when both zones of the dual completion are shut-in for pressure stabilization. Both zones shall remain shut-in until the well-head pressure in each has stabilized, provided however, that they need not remain shut-in more than seven days.
- 4. For Flow Test No. 1, one zone of the dual completion shall be produced at the normal rate of production while the other zone remains shut-in. Such test shall be continued for seven days in the case of a gas well and for 24 hours in the case of an oil well. Note: if, on an initial packer leakage test, a gas well is being flowed to the atmosphere due to lack of a pipeline connection the flow period shall be three hours.
- 5. Following completion of Flow Test No. 1, the well shall again be shut-in, in accordance with Paragraph 3 above.
- Flow Test No. 2 shall be conducted even though no leak was indicated during Flow Test No. 1. Procedure for Flow Test No. 2 is to be the same as for Flow Test No. 1 except

- that the previously produced zone shall remain shut-in while the zone which was previously shut-in is produced.
- 7. Pressures for gas-zone tests must be measured on each zone with a deadweight pressure gauge at time intervals as follows: 3 hours tests: intracdiately prior to the beginning of each flow period, at fifteen-minute intervals during the first hour thereof, and at hourly intervals thereafter, including one pressure measurement immediately prior to the conclusion of each flow period. 7-day tests: immediately prior to the beginning of each flow period, at least one time during each flow period (at approximately the midway point) and immediately prior to the conclusion of each flow period. Other pressures may be taken as desired, or may be requested on wells which have previously shown questionable test data.
- 24-hour oil zone tests: all pressures, throughout the entire test, shall be continuously measured and recorded with recording pressure gauges the accuracy of which must be checked at least twice, once at the beginning and once at the end of each test, with a deadweight pressure gauge. If a well is a gas-oil or an oil-gas dual completion, the recording gauge shall be required on the oil zone only, with deadweight pressures as required above being taken on the gas zone.
- 8. The results of the above-described tests shall be filed in triplicate within 15 days after completion of the test. Tests shall be filed with the Azteo District Office of the New Mexico Oil Conservation Division on Northwest New Mexico Packer Leakage Test Form Revised 10-01-78 with all deadweight pressures indicated thereon as well as the flowing temperatures (gas zones only) and gravity and GOR (oil zones only).