

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

30-045-24204

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. TYPE OF WORK DRILL ☒ DEEPEN ☐ PLUG BACK ☐

b. TYPE OF WELL  
OIL WELL ☐ GAS WELL ☒ OTHER ☐  
SINGLE ZONE ☒ MULTIPLE ZONE ☐

2. NAME OF OPERATOR  
Tenneco Oil Company

3. ADDRESS OF OPERATOR  
720 South Colorado Blvd., Denver, Colorado 80222

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.)  
At surface  
1750' FSL, 890' FEL  
At proposed prod. zone

14. DISTANCE IN MILES AND DIRECTION FROM NEAREST TOWN OR POST OFFICE\*  
5 Miles North West of Navajo Dam P.O.

15. DISTANCE FROM PROPOSED\*  
LOCATION TO NEAREST  
PROPERTY OR LEASE LINE, FT.  
(Also to nearest drlg. unit line, if any)

16. NO. OF ACRES IN LEASE  
1275.56

17. NO. OF ACRES ASSIGNED  
TO THIS WELL  
E/ 316.09

18. DISTANCE FROM PROPOSED LOCATION\*  
TO NEAREST WELL, DRILLING, COMPLETED,  
OR APPLIED FOR, ON THIS LEASE, FT.

19. PROPOSED DEPTH  
7520'

20. ROTARY OR CABLE TOOLS  
Rotary


21. ELEVATIONS (Show whether DF, RT, GR, etc.)  
6124 GR

22. APPROX. DATE WORK WILL START\*  
A.S.A.P.

23. PROPOSED CASING AND CEMENTING PROGRAM

SIZE OF HOLE	SIZE OF CASING	WEIGHT PER FOOT	SETTING DEPTH	QUANTITY OF CEMENT
13 3/4"	9 5/8" new	36#, K-55	+ 300'	Circulate to surface
8 3/4"	7" new	23#, K-55	+ 3600'	Circulate to surface
6 1/2"	4 1/2" new	10.5#, 11.6#	+ 7520'	Circulate to liner hanger

- 1) If non productive plug & abandon per U.S.G.S./BLM requirements.
- 2) No abnormal temperatures, pressures or other geologic hazards are expected
- 3) The gas is Dedicated



IN ABOVE SPACE DESCRIBE PROPOSED PROGRAM: If proposal is to deepen or plug back, give data on present or proposed new productive zone. If proposal is to drill or deepen directionally, give pertinent data on subsurface locations and measured and true depths. Give blowout preventer program, if any.

24. SIGNED *[Signature]* TITLE Staff Production Analyst DATE 1/25/80

(This space for Federal or State office use)

PERMIT NO. \_\_\_\_\_ APPROVAL DATE \_\_\_\_\_


APPROVED BY *[Signature]* TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY:

*wh Bond*

\*See Instructions On Reverse Side

NMOCC



## OIL CONSERVATION DIVISION

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENTP. O. BOX 7088  
SANTA FE, NEW MEXICO 87501Form C-107  
Revised 10-1-78

All distances must be from the outer boundaries of the Section.


Operator <b>TENNECO OIL COMPANY</b>			Lease <b>PRITCHARD</b>		Well No. <b>5-E</b>
Unit Letter <b>I</b>	Section <b>34</b>	Township <b>31N</b>	Range <b>9W</b>	County <b>San Juan</b>	
Actual Footage Location of Well: <b>1750</b> feet from the <b>South</b> line and <b>890</b> feet from the <b>East</b> line					
Ground Level Elev. <b>6124</b>	Producing Formation <b>Dakota</b>		Pool <b>Basin Dakota</b>		Dedicated Acreage: <b>316.09</b> Acres

1. Outline the acreage dedicated to the subject well by colored pencil or hatchure marks on the plat below.
2. If more than one lease is dedicated to the well, outline each and identify the ownership thereof (both as to working interest and royalty).
3. If more than one lease of different ownership is dedicated to the well, have the interests of all owners been consolidated by communitization, unitization, force-pooling, etc?

☐ Yes ☐ No If answer is "yes," type of consolidation \_\_\_\_\_

If answer is "no," list the owners and tract descriptions which have actually been consolidated. (Use reverse side of this form if necessary.) \_\_\_\_\_


No allowable will be assigned to the well until all interests have been consolidated (by communitization, unitization, forced-pooling, or otherwise) or until a non-standard unit, eliminating such interests, has been approved by the Commission.



## CERTIFICATION

I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief.

Name **M. Lee Freeman**  
Position **Staff Production Analyst**  
Company **Tenneco Oil Company**  
Date **1-25-80**



Date Surveyed **October 22, 1979**  
Registered Professional Engineer  
and/or Registered Surveyor  
**Fred E. Kerr Jr.**  
Certificate No. **39500**  
**STATE OF NEW MEXICO**  
**B. KERR, JR.**

# TEHNECO OIL COMPANY

## PROGNOSIS TO DRILL AND COMPLETE

DIVISION: Rocky Mountain

DATE: September 12, 1979

LEASE: Pritchard

WELL NO.: 5E

LOCATION: 1750' FSL, 890' FEL  
Sec. 34, T 31N, R 9W  
San Juan County, New Mexico

FIELD: Basin Dakota

ESTIMATED ELEVATION: 6140'

ESTIMATED TOTAL DEPTH: 7520'

PROJECTED HORIZON: Dakota

### DRILLING, CASING AND CEMENT PROGRAM:

- (1) MIRURT.
- (2) Drill a 13-3/4" hole to 300±. Run 9 5/8", 36#, K-55, ST&C casing to T.D. and cement to surface. Use 2% CaCl<sub>2</sub> in cement.
- (3) Cut off casing and weld on casing head. Pressure test weld to 1000 psi. NUBOP's and manifold. Pressure test casing, BOP's and manifold to 1000 psi for 30 minutes.
- (4) Drill out shoe and reduce hole to 8 3/4". Drill 8 3/4" hole to 3600±. Run 7", 23#, K-55, ST&C casing to T.D. and cement to surface. (Set 7" 200-300' into Lewis shale.)
- (5) Land casing is slips and cut off. Install drilling spool on casing head. Install rotating head, manifold and flare line. Pressure test blind rams, manifold and casing to 1000 psi for 15 minutes. Pick up drilling assembly and 3 1/2" drill
- (6) Drill out of 7" with 6 1/4" bit. Drill to within 5' of shoe and displace water with Nitrogen. Drill 5' of formation and blow with gas until well dusts. Drill to TD.
- (7) Log the hole dry as directed by the wellsite geological engineer and gauge the natural flow from the Dakota.
- (8) If productive, run 4 1/2" casing to T.D. as per casing design. Cement in one stage. Bring cement to above Mesaverde zone.
- (9) If nonproductive, plug and abandon as per U.S.G.S. requirements.

### ESTIMATED FORMATION TOPS: Surface formation San Jose

OJO Alamo	1670' (Water)	Point Look Out	5160' (Gas)
Pictured Cliffs	2930' (Gas)	Mancos	5540'
Lewis	3130' (Gas)	Gallup	
Cliffhouse	4720' (Gas)	Greenhorn	7200'
Menefee	4830' (Gas)	Dakota "A"	7310' (Gas)
		T.D.	7520'

### DRILLING MUD PROGRAM:

0 - 300' Spud Mud.

300' - 3600' Low solids fresh water mud. Use Benex to flocculate mud as needed.  
No WL control.

3600' - T.D. Gas.

### CORING AND TESTING PROGRAM:

No cores or tests.

### DEVIATION SURVEYS:

1. Survey surface hole at 100' intervals. Maximum allowable deviation at 250' is  $\frac{1}{2}^{\circ}$ .
2. FROM SURFACE TO TOTAL DEPTH DEVIATION SURVEYS MUST BE TAKEN EVERY 500' OR EACH TRIP WHICHEVER IS FIRST. This may entail running the TOTCO on wireline. Record each survey on the AAODC Drilling Report Sheet. Maximum allowable change in deviation is  $1^{\circ}$  per 100'.

### SAMPLES:

As directed by wellsite geological engineer.

### WELL SURVEYS:

Majority of logs will be cased hole GR - Neutron or TDT.

A few will be open hole GR - Induction.

### BOP:

PREVENTORS MUST BE CHECKED FOR OPERATION EVERY 24 HOURS, AND THE CHECK MUST BE RECORDED ON THE AAODC DRILLING REPORT SHEET.

## REPORTS

Drilling reports for the past 24 hours will include depth, footage, time distribution, activity breakdown, mud properties, bit record, bottom hole assembly, daily and cumulative mud costs, plus any other pertinent information; will be called into Tenneco Oil Company, Denver, Colorado between 7:30 A.M. and 8:00 A.M.

1. 303-758-7130 (office) - Don Barnes  
303-758-7287 - Don Barnes private line - Monday-Friday (before 7:45 A.M.)
2. 303-936-0704 (home) - Don Barnes - weekends and holidays
3. 303-795-0221 (home) - John Owen - if Don Barnes not available


The yellow sheet of the IADC Report to be filled out completely, the original copy of the drilling time recorder, and copies of any invoices from this well signed and received for Tenneco Oil Company will be mailed daily to:

TENNECO OIL COMPANY  
PENTHOUSE  
720 SOUTH COLORADO BOULEVARD  
DENVER, COLORADO 80222

ATTENTION: DRILLING DEPARTMENT

In case of an emergency, notify the following:

1. Mr. Don Barnes, Division Drilling Engineer - 303-936-0704.
2. Mr. John Owen, Project Drilling Engineer - 303-795-0221
3. Mr. Mike Lacey, Division Production Manager - 303-979-0509.



All equipment to be 3,000 psi working pressure except as noted.

- Rd Double ram type preventer with two sets of rams.
- R Single ram type preventer with one set of rams.
- S Drilling spool with side outlet connections for choke and kill lines.
- G Rotating head 150 psi working pressure minimum

#### ARRANGEMENT C

TENNECO OIL COMPANY  
 ROCKY MOUNTAIN DIVISION  
 REQUIRED MINIMUM  
 BLOWOUT PREVENTER AND  
 CHOKES MANIFOLD

1. Existing Road - Please refer to Map No. 1 which shows the existing roads. New roads which will be required have been marked on this map. All existing and new roads will be properly maintained during the duration of this project.
2. Planned Access Roads - Please refer to Map No. 1. The grade of the access roads will be consistent with that of the local terrain. The road surface will not exceed twenty feet (20') in width. Upon completion of the project, the access road will be adequately drained to control soil erosion. Drainage facilities may include ditches, water bars, culverts or any other measure deemed necessary by trained Company personnel to insure proper drainage. Gates and/or cattleguards will be installed if necessary.
3. Location of Existing Wells - Please refer to Map No. 2.
4. Location of Tank Batteries, Production Facilities, and Production Gathering and Service Lines - Please refer to Maps No. 1 and No. 2. Map No. 2 shows the existing roads and new proposed access roads. All known production facilities are shown on these two maps.
5. Location and Type of Water Supply - Water for the proposed project will be obtained from a private source.
6. Source of Construction Materials - No additional materials will be required to build either the access road or the proposed location.
7. Methods of Handling Waste Materials - All garbage and trash materials will be put into a burn pit shown on the attached Location Plat No. 1. When clean-up operations are begun on the proposed project, the burn pit with its refuse will be buried to a depth of at least three feet (3'). A latrine, the location of which is also shown on Plat No. 1. will be provided for human waste. If large amounts of liquids are left in the reserve pit after completion of the project, the pit will be fenced until the liquids have had adequate time to dry. The location clean-up will not take place until such time as the reserve pit can be properly covered over to prevent run-off from carrying any of these materials into the watershed. No earthen pit will be located on natural drainage; all earthen pits will be so constructed as to prevent leakage from occurring.

8. Ancillary Facilities - No camps or airstrips will be associated with this project.
9. Wellsite Layout - Please refer to the attached Plat No. 1.
10. Plans for Restoration of the Surface - After completion of the proposed project the location will be cleaned and leveled. The location will be left in such a condition that will enable reseeding operations to be carried out. Seed mixture as designated by the responsible government agency will be used. The reseeding operation will be performed during the time period set forth by the regulatory body. The location production equipment will be painted as designated by the responsible government agency.
11. Other Information - The proposed site is located adjacent to an existing location in Little Pump Canjon. The drainage pattern is Northerly through many erosional gullies. The soil is sandy loom. The principal vegetation types are sage, Oakbrush, salt bush, and native grasses.
12. Operator's Representative - See drilling prognosis.
13. Certification - I hereby certify that I, or persons under my direct supervision, have inspected the proposed drillsite and access route; that I am familiar with the conditions which presently exist; that the statements mad in this plan are, to the best of my knowledge, true and correct; and that the work associated with the operations proposed herein will be performed by Tenneco Oil Company and its contractors and sub-contractors in conformity with this plan and the terms and conditions under which it is approved.



L. Freeman  
Staff Production Analyst



# TENNECO OIL COMPANY

## CALCULATION SHEET

EXHIBIT

DRILLING WELL SITE LAYOUT *Pritchard SE*

*1750 FSL 890 FEL SEC 34, T31N, R9W* DATE *1-14-80*

*No New Road Construction, Adjacent to an existing location.*

*Place a diversion ditch around the south west end of the location draining to the north east.*

