

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

Tenneco Oil Company

3. ADDRESS OF OPERATOR

P.O.Box 3249, Englewood, Co 80155

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1090' FSL 1475' FWL "N"

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☒
☐
☐
☐
☐

(other) Csg.leak squeeze job #2

RECEIVED
JAN 8 1981
U. S. GEOLOGICAL SURVEY
FARMINGTON DISTRICT

(NOTE) Report results of multiple completion or zone change on Form 9-330

RECEIVED
JAN 8 1981
OIL CON. COM.
DIST. 3

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

12/11/80 TOH w/tbg. csg scraper and bit. TIH w/mtn.States Oil Tool tension pkr. Set pkr @ 5777'. RU Dowell and PT csg and CIBP below 5777' to 3500 PSI. Held OK. PT annulus to 3500 PSI. Lost 3000 PSI in 15mins. Found csg leak from 5617' to 5745'. PT tbg to 4500 PSI. Spotted 200 gals 7½% DI-HCL @ 5745' to cover 300' of 4½" csg. Reset pkr @ 4820'. PT annulus to 1500 PSI. Break down csg. leak @ 2200 PSI down tbg. Established rate: 3 BPM @ 1000PSI. ISIP: 100 PSI. Squeeze cmtd. csg. leak w/200sx CL-B containing 6½#/sk Gilsonite and 2% CACL₂. Leak squeezed off @ 2500 PSI. after appx. 170sx entered formation. Reversed tbg clean of cmt. water. Pulled 5 stands tbg. PT annulus to 1000PSI and tbg to 2500PSI.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Carly J. Smith TITLE Asst.Div.Adm.Mgr. DATE December 18, 1980

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

JAN 07 1981

FARMINGTON DISTRICT

*See Instructions on Reverse Side

NMOCC

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.