

NO. OF COPIES RECEIVED	3
DISTRIBUTION	
SANTA FE	1
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	1

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEFEY OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. ☐ OIL WELL ☒ GAS WELL ☐ OTHER-

2. Name of Operator
HALLAD OIL AND GAS CO.

3. Name of Operator
HALLAD OIL AND GAS CO.

4. Name of Well
UNIT LETTER I 1000 FEET FROM THE S LINE AND 1100 FEET FROM THE LINE, SECTION 19 TOWNSHIP 31N RANGE 13W N.M.P.M.

5a. Indicate Type of Lease
State ☐ Fee ☒

5. State Oil & Gas Lease No.

7. Unit Agreement Name

8. Farm or Lease Name
U.LINE

9. Well No.
1-M

10. Field and Pool, or Wildcat
BASIN BAYOTA-BLANCO SV

12. County
SAN JUAN

15. Elevation (Show whether DF, RT, GR, etc.)
1455 GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

☐ PERFORM REMEDIAL WORK
☐ TEMPORARILY ABANDON
☐ RILL OR ALTER CASING

☐ RILL AND ABANDON
☐ CHANGE PLANS

☐ REMEDIAL WORK
☐ COMMENCE DRILLING OPNS.
☐ CASING TEST AND CEMENT JOB
☐ OTHER

☐ ALTERING CASING
☐ PLUG AND ABANDONMENT

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-18-80 Spud 12-1/2" Surface. Drilled to 276'. Ran 6 ins., 2-5/8", 2 1/2" V-85 Casing. Set at 265' UB. Cement with 275 ex Glass LB with 2L Gel. and 1/2 Floreal per sack. Circulate 64 ex to surface.

5-1-80 Drilled 7-7/8" Hole to 6025'. Schlumberger ran ILS & CHL/FDC Logs.

5-2 Ran 172 ins., 5-1/2" 15.59 V-85. Set at 6031'. EV tools at 4793' and 2126'. Cemented first stage with 180 ex 50-50 poz, 2L gel, 6% Halad 9 and 1/2 Floreal per sack. Cemented second stage with 425 ex 50-50 poz, 2L gel, 6% Halad 9 and 1/2 Floreal per sack. Third stage with 250 ex 65-25 poz, 10% gel and 470 ex 50-50 poz, 2L gel and 6% Halad 9 and 1/2 Floreal per sack. Circulated 107 ex cement to surface. Plug down at 9:00 PM 5-1-80.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Original Signed by *ROBERT CHATEZ*

APPROVED BY: TITLE: DATE: MAY 1 1980

