

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well ☐ gas well ☐ other

2. NAME OF OPERATOR
CONSOLIDATED OIL AND GAS INC.

3. ADDRESS OF OPERATOR
P.O. BOX 2038 FARMINGTON, NEW MEXICO

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1450' FSL - 1195' FSL
AT TOP PROD. INTERVAL: 100'
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other) CEMENT JOB AND CEMENT PLUG	<input type="checkbox"/>	<input type="checkbox"/>

5. LEASE
SF 078464

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
CAIN

9. WELL NO.
1-M

10. FIELD OR WILDCAT NAME
BLANCO MESA VERDE BASIN DAKOTA

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
SEC. 25 - T31N - R13W

12. COUNTY OR PARISH
SAN JUAN

13. STATE
NEW MEXICO

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
5968' G.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

5-17-80 Drill 258' of 12-1/4" Hole. Ran 6 jts. new 8-5/8", 24#, K-55 Casing and cemented w/ 250 sx. 61 "B" - 1/4# floccal/ sx. Cir. 14 bbls cement.

5-31-80 Drill 7-7/8" Hole to 7125'. Log w/ Schlumberger, IBS/ FDL/ CNL.

5-31-80 Ran 181 jts. 5-1/2", 15.5#, K-55, 8rd ST & C Casing to 7118' w/ stage collar at 2416' and 4559'. Cemented 1st Stage w/ 100 sx 65-35, .6% gel followed w/ 250 sx 50-50 poz, 2% gel, .6% D-60, w/ 1/4# floccal/ sx. Cemented 2nd stage w/ 490 sx 50-50 poz, 2% gel, .6% D-60 w/ 1/4# floccal/ sx. Cemented 3rd Stage w/ 450 sx 65-35 poz, .6% gel followed w/ 180 sx 50-50 poz, 2% gel + .6% D-60, w/ 1/4# floccal/ sx. Plug Down 11:00 PM, 5-31-80

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED _____ TITLE Drilling Supt. DATE 6-4-80

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

ACCEPTED FOR RECORD
JUN 10 1980
FARMINGTON DISTRICT

